

Cisco.300-610.v2022-03-08.q110

Exam Code:	300-610
Exam Name:	Designing Cisco Data Center Infrastructure
Certification Provider:	Cisco
Free Question Number:	110
Version:	v2022-03-08
# of views:	2502
# of Questions views:	1100
https://www.freeqas.com/qa/Cisco/300-610/Cisco.300-610.v2022-03-08.q110.html	

NEW QUESTION: 1

DRAG DROP

A failure occurs on the network between two BFD and OSPF neighbors. Drag and drop the protocol actions from the left into the correct order on the right.

Select and Place:

Answer:

Section: Network Design

Explanation/Reference: https://www.cisco.com/c/en/us/td/docs/ios/12_0s/feature/guide/fs_bfd.html#wp1238898

NEW QUESTION: 2

Refer to the exhibit.

An engineer must assign multiple Fibre Channel IDs to a single port channel. Which two features must be enabled this goal? (Choose two.)

- A. SAN Pin Groups on the Cisco UCS Fabric Interconnects.
- B. NPV feature on the Cisco MDS Series.
- C. end-host mode feature on the Cisco UCS Fabric Interconnects
- D. NPIV feature on the Cisco MDS Series
- E. Smart Zoning feature on the Cisco UCS Fabric Interconnects

Answer: B,D (LEAVE A REPLY)

Section: Compute Design

NEW QUESTION: 3

Which feature provides a sandbox to convert NX-OS CLI commands to REST-based scripts on Cisco Nexus 7700 Series Switches?

- A. Guest shell
- B. NX-API
- C. Postman

D. Bash shell

Answer: B ([LEAVE A REPLY](#))

NEW QUESTION: 4

When planning to deploy a load-balancing service as a managed node, which ACI configuration must be included?

A. BGP ECMP

B. Layer 4 to Layer 7 device package

C. inline load-balancing device

D. ITD

Answer: ([SHOW ANSWER](#))

Section: Network Design

Explanation/Reference: https://www.cisco.com/c/en/us/td/docs/switches/datacenter/aci/apic/sw/1-x/ACI_Best_Practices/b_ACI_Best_Practices/b_ACI_Best_Practices_chapter_0110.html

NEW QUESTION: 5

When planning to deploy a load-balancing service as a managed node, which ACI configuration must be included?

A. ITD

B. inline load-balancing device

C. BGP ECMP

D. Layer 4 to Layer 7 device package

Answer: D ([LEAVE A REPLY](#))

NEW QUESTION: 6

Which two types of service profile templates does Cisco UCS support? (Choose two.)

A. updating

B. connected

C. temporary

D. permanent

E. initial

Answer: A,E ([LEAVE A REPLY](#))

NEW QUESTION: 7

A network engineer must design a Cisco HyperFlex solution based on these requirements:

* two clusters in the main data center consisting of five HyperFlex nodes

* one edge node for the remote branch

* cluster nodes that use one rack unit of space

Which two devices should be used in the remote branch cluster for this design? (Choose two.)

A. Fabric Interconnect 6300

B. HX220c

C. Gigabit Ethernet Switch

D. HX240c

E. UCS B200

Answer: D,E ([LEAVE A REPLY](#))

NEW QUESTION: 8

An engineer deploys LISP VM mobility. Which feature is configured on the interfaces that have VM mobility enabled?

- A. IP redirects
- B. flow control
- C. proxy ARP
- D. HSRP

Answer: ([SHOW ANSWER](#))

Section: Network Design

Explanation/Reference: https://www.cisco.com/c/en/us/td/docs/switches/datacenter/sw/nx-os/lisp/configuration/guide/b_NX-OS_LISP_Configuration_Guide/b_NX-OS_LISP_Configuration_Guide_chapter_010.html

NEW QUESTION: 9

Which two automation requirements can be met by using Puppet? (Choose two.)

- A. Enable one-off infrastructure changes to be performed manually.
- B. Enable clients to pull changes to configuration files.
- C. Push configuration updates immediately to servers.
- D. Provide support for writing new modules in Python.
- E. Enable clients to pull changes without installing an agent.

Answer: B,C ([LEAVE A REPLY](#))

NEW QUESTION: 10

What can be implemented on Cisco Nexus 5600 Series Switches for link redundancy within a Fibre Channel fabric?

- A. vPC+
- B. E-Trunk
- C. LACP port channel
- D. SAN port channel

Answer: ([SHOW ANSWER](#))

NEW QUESTION: 11

An engineer manages hundreds of Cisco Nexus Series and 9000 Series Switches that are installed at several data centers and wants to use one of the built-in automation tools of the Cisco NX-OS Guest Shell to automate daily activities. The engineer requires a tool that uses imperative language, has extensive support, and is object-oriented. Which automation tool should be used to meet these requirements?

- A. Python
- B. Bash
- C. YAML
- D. Perl

Answer: A ([LEAVE A REPLY](#))

Python is object-oriented and imperative language.

YAML is declarative.

NEW QUESTION: 12

An engineer must configure an interface for managing and orchestrating a Cisco Nexus device. The interface must be operational if the data and control planes crash, support IPv4 and IPv6 addressing, and have access to its own VRF instance.

Which interface should be used to meet these requirements?

- A. loopback interface
- B. management interface
- C. interface VLAN
- D. physical interface

Answer: B ([LEAVE A REPLY](#))

NEW QUESTION: 13

Drag and drop the components from the left onto the descriptions on the right that indicate what occurs to Fibre Channel fabric when that component fails.

Answer:

NEW QUESTION: 14

A failure occurs on the network between two BFD and OSPF neighbors. Drag and drop the protocol actions from the left into the correct order on the right.

Answer:

NEW QUESTION: 15

A Cisco UCS instance has four interfaces on a UCS VIC. Where on the fabric interconnect does each interface terminate?

- A. vPC
- B. physical port
- C. virtual interface
- D. port channel

Answer: C ([LEAVE A REPLY](#))

NEW QUESTION: 16

Drag and drop the data center technologies from the left onto the correct descriptions on the right. Not all technologies are used.

Answer:

Valid 300-610 Dumps shared by PrepPdf.com for Helping Passing 300-610 Exam! PrepPdf.com now offer the **newest 300-610 exam dumps**, the PrepPdf.com 300-610 exam **questions have been updated** and **answers have been corrected** get the **newest**

NEW QUESTION: 17

Which mode must be enabled on a Cisco UCS Fabric Interconnect to connect directly to a storage array?

- A. NPV mode
- B. NPIV mode
- C. FC end-host mode
- D. FC switching mode

Answer: ([SHOW ANSWER](#))

NEW QUESTION: 18

A customer must install a new Hyperflex Stretched cluster in two sites. Low latency and predictable high performance are the top priorities for this setup due to the extensive usage of data-intensive applications across the cluster. Which HyperFlex storage solution is recommended to meet these requirements?

- A. All-HDD
- B. Hybrid
- C. All-SAN
- D. All-Flash

Answer: D ([LEAVE A REPLY](#))

NEW QUESTION: 19

Which two vSphere features must be included in the design of a Cisco HyperFlex systems stretched cluster?

(Choose two.)

- A. VDP
- B. DRS
- C. FT
- D. VSS
- E. HA

Answer: ([SHOW ANSWER](#))

NEW QUESTION: 20

An engineer installs a B-Series server in a Cisco UCS chassis that contains a pair of UCS-IOM-2208XP I/O modules. The full bandwidth of the I/O module must be utilized. Which two elements should be used in this environment? (Choose two.)

- A. eight twinax cables from each I/O module to each fabric interconnect
- B. four twinax cables from each I/O module to each fabric Interconnect
- C. Cisco UCS VIC 1225
- D. Cisco UCS M81KR
- E. Cisco UCS VIC 1280

Answer: A,E ([LEAVE A REPLY](#))

2208 has 8 uplinks. VIC 1225 only works on C-Series UCS. M81KR has only 2x10G ports. VIC 1280 has 8x10G ports.

NEW QUESTION: 21

An engineer installs a B-Series server in a Cisco UCS chassis that contains a pair of UCS-IOM-2208XP I/O modules. The full bandwidth of the I/O module must be utilized.

Which two elements should be used in this environment? (Choose two.)

- A. eight twinax cables from each I/O module to each fabric interconnect
- B. four twinax cables from each I/O module to each fabric interconnect
- C. Cisco UCS VIC 1225
- D. Cisco UCS VIC 1280
- E. Cisco UCS M81KR

Answer: A,D (LEAVE A REPLY)

NEW QUESTION: 22

A client in a commercial building installs a Cisco blade server in the multitenant Cisco UCS blade Infrastructure. To cut operating costs the client's data center is shared with other organizations. The client asks an engineer prevent third parties from accessing their equipment and from accessing BIOS-related information when booting a server. Which Two policies must be used to meet these requirements? (Choose two.)

- A. quiet boot
- B. post error pause
- C. ASPM support
- D. CDN control
- E. front panel lockout

Answer: A,D (LEAVE A REPLY)

Reference:

https://www.cisco.com/c/en/us/td/docs/unified_computing/ucs/ucs-manager/GUI-User-Guides/Server-Mgmt/3-2/b_Cisco_UCS_Manager_Server_Mgmt_Guide_3_2/b_Cisco_UCS_Manager_Server_Mgmt_Guide_3_2_chapter_01110.html

Quiet boot is what the BIOS displays during booting the server. If enabled, the BIOS displays the logo screen.

I believe that quiet boot and CDN control may have the customer name.

NEW QUESTION: 23

A network architect proposes a distinct Fibre Channel fabric to be used for a Cisco UCS blade server that hosts critical applications. Which action should be implemented for the Fibre Channel traffic from the vHBA of this server to pass through the I/O Module in the Cisco UCS chassis to a specified uplink Fibre Channel port?

- A. Update the applied Fibre Channel adapter policy.
- B. Update the applied global QoS policy.
- C. Include a SAN pin group in the vHBA policy.
- D. Enable Persistent Binding in the vHBA policy.

Answer: A (LEAVE A REPLY)

NEW QUESTION: 24

What are two functions of a Network Services Orchestrator in an NFV environment? (Choose two.)

- A. It operates at the resource-facing services layer and provides overall lifecycle management at the network service level.
- B. It provides an API-based northbound interface for transparent integration with systems that operate at the resource-facing services layer.
- C. It provides a standards-based southbound interface for transparent integration with systems that operate at the customer-facing services layer.
- D. It provides a standards-based northbound interface for transparent integration with systems that operate at the customer-facing services layer.
- E. It operates at the customer-facing services layer and provides the management interface for the virtual network devices.

Answer: ([SHOW ANSWER](#))

Section: Automation Design

Explanation/Reference: https://www.cisco.com/c/en/us/td/docs/net_mgmt/msx/3_4/solution_overview/Cisco_VMS_Sol_Overview.pdf

NEW QUESTION: 25

Which two features are provided by deploying an OOB management network in a Cisco Nexus data center? (Choose two.)

- A. Layer 3 path for vPC keepalive packets
- B. Layer 2 path for a vPC peer link
- C. Layer 2 path for server traffic
- D. Layer 3 path for server traffic
- E. Layer 3 path for monitoring purposes

Answer: ([SHOW ANSWER](#))

NEW QUESTION: 26

Which two configuration methods can be used to deploy QoS to Cisco MDS Series switches? (Choose two.)

- A. VSAN-based QoS
- B. zone-based QoS
- C. multiple QoS policies that match individual devices
- D. multiple QoS policies that match multiple devices
- E. FCoE VLAN-based QoS

Answer: ([SHOW ANSWER](#))

NEW QUESTION: 27

DRAG DROP

Drag and drop the technologies from the left onto the correct descriptions on the right.

Select and Place:

Answer:

Section: Storage Network Design

NEW QUESTION: 28

Drag and drop the data center technologies from the left onto the correct descriptions on the right. Not all technologies are used.

Answer:

NEW QUESTION: 29

An engineer wants to eliminate the manual process of checking the system hardware and firmware against a specified hardware compatibility tool. The tool must be able to manage an extensive list of devices including Cisco HyperFlex, MDS, and Nexus switches. The tool must manage hardware in multiple data centers so it should be deployed on public cloud infrastructure.

Which tool meets these requirements?

- A. Cisco Tetration
- B. Cisco Data Center Network Manager
- C. Cisco UCS Director
- D. Cisco Intersight

Answer: D (LEAVE A REPLY)

D18912E1457D5D1DDCBD40AB3BF70D5D

NEW QUESTION: 30

A network engineer is implementing Cisco UCS manager with Cisco UCS center integration. The company is strict security policies require that the logical profile of virtual network adapters and logical addressing assigned to Cisco UCS servers be managed by the Cisco UCS manager. The users must also be prevented from being able to acknowledge pending activities in the Cisco UCS manager.

Which two profile must be used to meet these requirements? (Choose two.)

- A. Global maintenance
- B. Public network control
- C. Restricted chassis
- D. Local power
- E. Local service

Answer: (SHOW ANSWER)

https://www.cisco.com/c/en/us/td/docs/unified_computing/ucs/ucs-central/GUI-User-Guides/Operations/b_UCSC_Ops_Guide/b_UCSC_Ops_Guide_chapter_0111.html#id_16185

NEW QUESTION: 31

Which two configuration methods can be used to deploy QoS to Cisco MDS Series switches? (Choose two.)

- A. zone-based QoS
- B. multiple QoS policies that match individual devices
- C. VSAN-based QoS
- D. FCoE VLAN-based QoS
- E. multiple QoS policies that match multiple devices

Answer: A,C (LEAVE A REPLY)

Section: Storage Network Design

Explanation/Reference: https://www.cisco.com/c/en/us/td/docs/switches/datacenter/mds9000/sw/7_3/configuration/qos/cisco_mds9000_qos_config_guide/configuring_qos.html

Valid 300-610 Dumps shared by PrepPdf.com for Helping Passing 300-610 Exam! PrepPdf.com now offer the **newest 300-610 exam dumps**, the PrepPdf.com 300-610 exam **questions have been updated** and **answers have been corrected** get the **newest** PrepPdf.com 300-610 dumps with Test Engine here: <https://www.preppdf.com/Cisco/300-610-prepaway-exam-dumps.html> (330 Q&As Dumps, **40%OFF Special Discount: Exam-Tests**)

NEW QUESTION: 32

An engineer is expanding an existing iSCSI environment and must choose an addressing scheme. When checking one of the devices, the engineer discovers this target device naming used

{prefix}. 2019-01.com.acme.123:00.ftd0cb21.bcb389458389

Which addressing scheme was used in the environment?

- A. Network Address Authority
- B. iSCSI Qualified Name
- C. Extended Unique identifier
- D. Fibre Channel ID

Answer: B (LEAVE A REPLY)

NEW QUESTION: 33

Drag and drop the SAN components from the left onto the correct design considerations on the right.

Answer:

NEW QUESTION: 34

An engineer must use OTV for Layer 2 connectivity between data centers to support virtual machine mobility between the customer sites. To support this requirement, the engineer must ensure the existence of the same default gateway on both sites. Additionally, the operations team reports high bandwidth utilization on site A and wants to optimize the outbound traffic flows to use a local DC exit point. Which feature must be used to meet these requirements?

- A. control group
- B. data group
- C. ARP filter
- D. FHRP filter

Answer: A (LEAVE A REPLY)

NEW QUESTION: 35

An engineer manages hundreds of Cisco Nexus 3000 Series and 9000 Series Switches that are installed at several data centers and wants to use one of the built-in automation tools of the Cisco NX-OS Guest Shell to automate daily activities. The engineer requires a tool that uses imperative language, has extensive library support, and is object-oriented.

Which automation tool should be used to meet these requirements?

- A. Python
- B. Bash
- C. Perl
- D. YAML

Answer: A ([LEAVE A REPLY](#))

D18912E1457D5D1DDCBD40AB3BF70D5D

NEW QUESTION: 36

Which two configurations allow for routing traffic between two VDCs? (Choose two.)

- A. Connect the VDCs to an external Layer 3 device.
- B. Cross-connect the ports between the VDCs.
- C. Create interfaces in the VDC that can be accessed by another VDC.
- D. Create a policy map in the default VDC that routes traffic between the VDCs.
- E. Create VRF-aware software infrastructure interfaces.

Answer: A,D ([LEAVE A REPLY](#))

NEW QUESTION: 37

What are two functions of a Network Services Orchestrator in an NFV environment? (Choose two.)

- A. It operates at the customer-facing services layer and provides the management interface for the virtual network devices.
- B. It provides a standards-based southbound interface for transparent integration with systems that operate at the customer-facing services layer.
- C. It operates at the resource-facing services layer and provides overall lifecycle management at the network service level.
- D. It provides a standards-based northbound interface for transparent integration with systems that operate at the customer-facing services layer.
- E. It provides an API-based northbound interface for transparent integration with systems that operate at the resource-facing services layer.

Answer: C,E ([LEAVE A REPLY](#))

NEW QUESTION: 38

Drag and drop the Cisco Nexus 7000 Series Switch resources from the left onto the correct groups on the right.

Answer:

NEW QUESTION: 39

A customer needs to deploy a three-tier network architecture that will consist of web, and other business-critical applications. The solution will include Cisco UCS 6324 Fabric interconnects managing B and C Series servers. The Fabric interconnects will be connected to the Cisco Nexus 7706 series switch for network access. A storage array will be directly connected to the UCS deployment. Which type must be used to meet these requirements?

- A. UCS Interconnect in Ethernet end-host mode
UCS Interconnect in Fibre Channel switching mode
Fabric Interconnects uplinked to the Nexus device using an LACP port-channel in active mode
- B. UCS Interconnect in Ethernet switching mode
UCS interconnect to Fibre Channel switching mode
Fabric Interconnect uplinked to the Nexus device using an LACP port-channel in passive mode
- C. UCS Interconnect in Ethernet end-host mode
UCS Interconnect in Fibre Channel end-host mode

Fabric Interconnect uplinked to me Nexus device using an LACP port-channel in passive mode

D. UCS Inter conned in Ethernet switching mode

UCS interconnect in Fibre Channel end-host mode

Fabric Interconnects uplinked to the Nexus device using an LACP port-channel in active mode

Answer: [\(SHOW ANSWER\)](#)

FC must be in switching mode for Direct Attached Storage.

NEW QUESTION: 40

Refer to the exhibit.

The FCoE packets fail to be forwarded through the switch. What is the minimum MTU QoS requirement for the FCoE to work?

A. 2000 bytes

B. 2240 bytes

C. 2158 bytes

D. 9000 bytes

Answer: **A** [\(LEAVE A REPLY\)](#)

NEW QUESTION: 41

Drag and drop the components from the left onto the descriptions on the right that indicate what occurs to Fibre Channel fabric when that component fails.

Answer:

NEW QUESTION: 42

An engineer configured the OSPF protocol in the vPC topology. During the catastrophic failure of one of the vPC member switches, the traffic was routed to a black hole. This route was caused by the long convergence time caused by the delay of the vPC member switch reboot. After the failure, the engineer rebooted both switches, but the secondary switch powered on before the primary one. It caused all the vPCs to be shut down due to consistency-check violations.

Which two features must be used to prevent these situations from happening in the future? (Choose two.)

A. auto-recovery

B. system priority

C. delay restore

D. peer-gateway

E. ip arp synchronize

Answer: **A,C** [\(LEAVE A REPLY\)](#)

NEW QUESTION: 43

An engineer must design a Cisco UCS environment that will connection to a storage area network. The solution must include support for these conditions:

* connectivity to the existing 10 Gigabit Ethernet network

* booting the server infrastructure from the network

* integration with the existing Fibre Channel storage arrays

* lossless data transfer

Which solution should be used to meet these requirements?

- A. NFS
- B. FCoE
- C. CIFS
- D. FCP

Answer: ([SHOW ANSWER](#))

NEW QUESTION: 44

What are two reasons to select OTV as the DCI solution to connect multisite topologies? (Choose two.)

- A. It extends the spanning tree between data centers.
- B. It constrains HSRP hello messages to each data center.
- C. It propagates hosts reachability without support of traffic flooding.
- D. It is an open standard.
- E. Layer 3 failures do not propagate beyond the OTV edge device.

Answer: A,E ([LEAVE A REPLY](#))

NEW QUESTION: 45

Refer to the exhibit.

The FCoE packets fail to be forwarded through the switch. What is the minimum MTU QoS requirement for the FCoE to work?

- A. 2240 bytes
- B. 9000 bytes
- C. 2158 bytes
- D. 2000 bytes

Answer: ([SHOW ANSWER](#))

NEW QUESTION: 46

Drag the appropriate from the left onto the current UDLD modes of operation on the right.

Answer:

Valid 300-610 Dumps shared by PrepPdf.com for Helping Passing 300-610 Exam! PrepPdf.com now offer the **newest 300-610 exam dumps**, the PrepPdf.com 300-610 exam **questions have been updated** and **answers have been corrected** get the **newest** PrepPdf.com 300-610 dumps with Test Engine here: <https://www.preppdf.com/Cisco/300-610-prepaway-exam-dumps.html> (**330** Q&As Dumps, **40%OFF Special Discount: Exam-Tests**)

NEW QUESTION: 47

A failure occurs on the network between two BFD and OSPF neighbors. Drag and drop the protocol actions from the left into the correct order on the right.

Answer:

NEW QUESTION: 48

DRAG DROP

Drag and drop the feature descriptions from the left onto the correct UCS Fabric Interconnect modes on the right.

Select and Place:

Answer:

Section: Compute Design

Explanation/Reference: https://www.cisco.com/c/en/us/solutions/collateral/data-center-virtualization/unified-computing/whitepaper_c11-701962.html**NEW QUESTION: 49**

Which two methods mitigate congestion in a SAN network? (Choose two.)

- A. Configure ER_RDY to allow splitting of each ISL between switches into separate virtual links.
- B. Use the port-monitor command to detect slow drain devices.
- C. Configure the port channel to enable individual buffer-to-buffer credits.
- D. Configure the port monitor to allow categorization of a specific device as slow.
- E. Configure the flow control for the FC to use R_RDY.

Answer: (SHOW ANSWER)

Section: Storage Network Design

Explanation/Reference: https://www.cisco.com/c/en/us/td/docs/switches/datacenter/mds9000/sw/8_x/config/interfaces/cisco_mds9000_interfaces_config_guide_8x/congestion_avoidance_isolation.html**NEW QUESTION: 50**

A company must introduce a scalable network automation tool to deploy, configure, and manage thousands of network devices and servers. The company servers already have been security-hardened and must not have any additional software installed on them. The security policy mandates the use of a secure communication protocol that supports authentication and encryption for managing the servers.

Which two automation tools must be used to meet these requirements? (Choose two.)

- A. Puppet
- B. SaltStack
- C. CFEngine
- D. Chef
- E. Ansible

Answer: A,B (LEAVE A REPLY)**NEW QUESTION: 51**

A client in a commercial building installs a Cisco blade server in the multitenant Cisco UCS blade Infrastructure. To cut operating costs the client's data center is shared with other organizations. The client asks an engineer prevent third parties from accessing their equipment and from accessing BIOS-related information when booting a server. Which Two policies must be used to meet these requirements? (Choose two.)

- A. quiet boot
- B. post error pause

- C. ASPM support
- D. CDN control
- E. front panel lockout

Answer: A,D (LEAVE A REPLY)

https://www.cisco.com/c/en/us/td/docs/unified_computing/ucs/ucs-manager/GUI-User-Guides/Server-Mgmt/3-2/b_Cisco_UCS_Manager_Server_Mgmt_Guide_3_2/b_Cisco_UCS_Manager_Server_Mgmt_Guide_3_2_chapter_01110.html

Quiet boot is what the BIOS displays during booting the server. If enabled, the BIOS displays the logo screen.

I believe that quiet boot and CDN control may have the customer name.

NEW QUESTION: 52

An engineer designs a Cisco UCS solution that must provide guaranteed and deterministic bandwidth to a specific server in the environment. The solution must apply to network and storage traffic of C-Series and BSeries servers.

Which solution should be included to meet these requirements?

- A. Pin the server ports of the service profile to dedicated uplink ports.
- B. Pin the IOM ports of the service profile to dedicated server ports.
- C. Pin the vNICs and vHBAs of the service profile to dedicated server ports.
- D. Pin the vNICs and the vHBAs of the service profile to dedicated uplink ports.

Answer: A (LEAVE A REPLY)

NEW QUESTION: 53

Refer to the exhibit.

An engineer must assign multiple Fibre Channel IDs to a single port channel. Which two features must be enabled this goal? (Choose two.)

- A. Smart Zoning feature on the Cisco UCS Fabric Interconnects
- B. NPIV feature on the Cisco MDS Series
- C. NPV feature on the Cisco MDS Series.
- D. end-host mode feature on the Cisco UCS Fabric Interconnects
- E. SAN Pin Groups on the Cisco UCS Fabric Interconnects.

Answer: B,C (LEAVE A REPLY)

NEW QUESTION: 54

Drag and drop the configurations from the left onto the correct policies on the right.

Answer:

NEW QUESTION: 55

Which two methods mitigate congestion in a SAN network? (Choose two.)

- A. Configure ER_RDY to allow splitting of each ISL between switches into separate virtual links.
- B. Use the port-monitor command to detect slow drain devices.
- C. Configure the port channel to enable individual buffer-to-buffer credits.
- D. Configure the port monitor to allow categorization of a specific device as slow.
- E. Configure the flow control for the FC to use R_RDY.

Answer: B,D (LEAVE A REPLY)

Reference:

[cisco_mds9000_interfaces_config_guide_8x/congestion_avoidance_isolation.html](https://www.cisco.com/c/en/us/support/docs/ios-nx-os-software/nx-os-software/212589-understanding-vpc-election-process.html)

NEW QUESTION: 56

An engineer configured the OSPF protocol in the vPC topology. During the catastrophic failure of one of the vPC the member switches, the traffic was routed to a black hole. This route was caused by the long convergence time caused by the delay of the of the vPC member switch reboot. After the failure, the engineer rebooted both switches, but the secondary switch powered on before the primary one. It caused all the vPCs to be shut down due to consistency-check violations. Which two features must be used to prevent these situations from happening in the future? (Choose two.)

- A. auto-recovery
- B. system priority
- C. delay restore
- D. ip arp synchronize
- E. peer-gateway

Answer: A,C (LEAVE A REPLY)

System priority is related to LACP, not vPC, so it is out. ARP s

Reference:

<https://www.cisco.com/c/en/us/support/docs/ios-nx-os-software/nx-os-software/212589-understanding-vpc-election-process.html>

NEW QUESTION: 57

A failure occurs on the network between two BFD and OSPF neighbors. Drag and drop the protocol actions from the left into the correct order on the right.

Answer:

NEW QUESTION: 58

A network architect must design a large-scale Cisco SAN topology. The customer has a limited budget, so a design that provides use of resources is required. To support this requirement, the architect to share array ports, ISL, and line card bandwidth. The customer has also presented these additional considerations:

The customers plans to expand the network by 10% over the next two years.

The customer's policy requires physically separated infrastructure to support high availability.

Which solution should be used to meet these requirements?

- A. Collapsed-core
- B. Mesh
- C. Core-edge
- D. Edge-core-edge

Answer: (SHOW ANSWER)

Please review this question.

NEW QUESTION: 59

Drag and drop the Cisco Nexus 7000 Series Switch resources from the left onto the correct groups on the right.

Answer:

NEW QUESTION: 60

What is an advantage of using OTV as compared to VPLS for data center redundancy?

- A. uses a proactive MAC advertisement
- B. prevents loops on point-to-point links
- C. provides head-end replication
- D. provides full-mesh connectivity

Answer: ([SHOW ANSWER](#))

NEW QUESTION: 61

Which Cisco HyperFlex feature provides virtual machine-level cost scaling for desktop virtualization growth?

- A. HyperFlex Edge support
- B. encryption offload cards
- C. dedicated compute nodes
- D. fabric interconnects

Answer: A ([LEAVE A REPLY](#))

Section: Compute Design

Valid 300-610 Dumps shared by PrepPdf.com for Helping Passing 300-610 Exam! PrepPdf.com now offer the **newest 300-610 exam dumps**, the PrepPdf.com 300-610 exam **questions have been updated** and **answers have been corrected** get the **newest** PrepPdf.com 300-610 dumps with Test Engine here: <https://www.preppdf.com/Cisco/300-610-prepaway-exam-dumps.html> (**330 Q&As Dumps, 40%OFF Special Discount: Exam-Tests**)

NEW QUESTION: 62

Drag and drop the technologies from the left onto the correct descriptions on the right.

Answer:

NEW QUESTION: 63

An engineer configured the OSPF protocol in the vPC topology. During the catastrophic failure of one of the vPC the member switches, the traffic was routed to a black hole. This route was caused by the long convergence time caused by the delay of the of the vPC member switch reboot. After the failure, the engineer rebooted both switches, but the secondary switch powered on before the primary one. It caused all the vPCs to be shut down due to consistency-check violations. Which two features must be used to prevent these situations from happening in the future? (Choose two.)

- A. auto-recovery
- B. system priority
- C. delay restore
- D. ip arp synchronize
- E. peer-gateway

Answer: A,C ([LEAVE A REPLY](#))

System priority is related to LACP, not vPC, so it is out. ARP s

<https://www.cisco.com/c/en/us/support/docs/switches/nexus-7000-series-switches/116187-configure-vpc-00.html>

<https://www.cisco.com/c/en/us/support/docs/ios-nx-os-software/nx-os-software/212589-understanding-vpc-election-process.html>

NEW QUESTION: 64

A failure occurs on the network between two BFD and OSPF neighbors. Drag and drop the protocol actions from the left into the correct order on the right.

Answer:

NEW QUESTION: 65

An engineer deploys LISP VM mobility. Which feature is configured on the interfaces that have VM mobility enabled?

- A. flow control
- B. HSRP
- C. IP redirects
- D. proxy ARP

Answer: ([SHOW ANSWER](#))

NEW QUESTION: 66

An engineer is designing a data center that uses FCIP. How is QoS configured in this environment?

- A. A separate DSCP value and CoPP must be configured for all FCIP traffic and another for all of the FCIP in the data connection.
- B. A separate DSCP value must be configured for all FCIP VSAN traffic.
- C. A separate DSCP value and priority queuing must be configured for all FCIP traffic.
- D. Two separate DSCP values must be configured, one for all of the FCIP frames in the control TCP connection and another for all of the FCIP frames in the data connection.

Answer: D ([LEAVE A REPLY](#))

Section: Storage Network Design

Explanation/Reference: https://www.cisco.com/c/en/us/td/docs/switches/datacenter/mds9000/sw/5_0/configuration/guides/ipsvc/nxos/ipsvc/cfcip.html

NEW QUESTION: 67

After experiencing traffic disruptions from the failure of a single router, a customer asks an engineer to design a solution that will prevent this from occurring in the future. While examining the customer's environment, the engineer discovers that the routers are manufactured by a variety of different vendors, and they have varying amounts of CPU and memory resources. Additionally, several of the customer's applications require the ability to fine-tune the load-balancing parameters between multiple routers. Which solution should be used to meet these requirements?

- A. VRRP
- B. GLBP
- C. FHRP
- D. HSRP

Answer: A ([LEAVE A REPLY](#))

Load balancing can be done by having different VRRP groups and configuring different servers with different default gateways. HSRP and GLBP are Cisco proprietary.

NEW QUESTION: 68

Refer to the exhibit.

A Cisco UCS chassis that has two IOMs is discovered. The chassis discovery policy creates a fabric port channel. What is the result of this policy?

- A. Each uplink that connects an IOM is configured as a discrete link.
- B. The port channel is disabled until an administrator enables it manually.
- C. Cisco UCS Manager creates a single fabric port channel.
- D. Cisco UCS Manager creates two separate fabric port channels.

Answer: D (LEAVE A REPLY)

NEW QUESTION: 69

What is the disadvantage of asynchronous storage replication as compared to synchronous storage replication in a disaster recovery design?

- A. reduction in application performance
- B. distance limitations
- C. specific backup requirements
- D. potential data loss

Answer: D (LEAVE A REPLY)

Section: Storage Network Design

Explanation/Reference: <https://www.evidian.com/products/high-availability-software-for-application-clustering/synchronous-replication-vs-asynchronous-replication/>

NEW QUESTION: 70

An engineer is experiencing performance issues on a Cisco UCS blade server. The B-series blade server contains four CPUs, most of which are idle. The engineer notices that the CPU is suffering from too many requests sent by the NIC. Additionally, the number of queues appears to be insufficient and only a single CPU is processing the network traffic. Which policy must be used to alleviate these issues?

- A. Ethernet adapter
- B. vNIC placement
- C. LAN connectivity
- D. Dynamic vNIC connection

Answer: A (LEAVE A REPLY)

https://www.cisco.com/en/US/docs/unified_computing/ucs/sw/gui/config/guide/141/UCSM_GUI_Configuration_Guide_141_chapter19.html

Ethernet adapter policy is the only policy that is having configuration that is related to CPU.

NEW QUESTION: 71

Drag and drop the Cisco Nexus 7000 Series Switch resources from the left onto the correct groups on the right.

Answer:

NEW QUESTION: 72

Which two configurations are available by using a service profile template in Cisco UCS Manager? (Choose two.)

- A. number of vHBAs
- B. ARP entries
- C. UUID assignment
- D. VXLAN membership
- E. target server

Answer: (SHOW ANSWER)

Section: Automation Design

Explanation/Reference: https://www.cisco.com/c/en/us/td/docs/unified_computing/ucs/sw/cli/config/guide/2-2/b_UCSM_CLI_Configuration_Guide_2_2/b_UCSM_CLI_Configuration_Guide_2_2_chapter_0100000.html

NEW QUESTION: 73

Refer to the exhibit.

Which template is used when a vHBA template pair is created for a specific server that inherits its attributes from an existing template?

- A. Secondary
- B. Initial
- C. Updating
- D. Primary

Answer: (SHOW ANSWER)

Section: Automation Design

NEW QUESTION: 74

An engineer is implementing management access to a Cisco Nexus platform. The customer requires a solution that provides isolation between the data and control planes, in addition to management that uses encryption and authentication. The customer will manage the device using both IPv4 and IPv6.

Which two components should be used to meet these requirements? (Choose two.)

- A. mgmt0 interface
- B. SVI interface
- C. SSH protocol
- D. SNMP
- E. Telnet protocol

Answer: (SHOW ANSWER)

NEW QUESTION: 75

An engineer is experiencing performance issues on a Cisco UCS blade server. The B-Series blade server contains four CPUs, most of which are idle. The engineer notices that the CPU is suffering from too many requests sent by the NIC. Additionally, the number of queues appears to be insufficient and only a single CPU is processing the network traffic.

Which policy must be used to alleviate these issues?

- A. Ethernet adapter

- B. vNIC placement
- C. dynamic vNIC connection
- D. LAN connectivity

Answer: C (LEAVE A REPLY)

NEW QUESTION: 76

Drag and drop the SAN components from the left onto the correct design considerations on the right.

Answer:

Valid 300-610 Dumps shared by PrepPdf.com for Helping Passing 300-610 Exam! PrepPdf.com now offer the **newest 300-610 exam dumps**, the PrepPdf.com 300-610 exam **questions have been updated** and **answers have been corrected** get the **newest** PrepPdf.com 300-610 dumps with Test Engine here: <https://www.preppdf.com/Cisco/300-610-prepaway-exam-dumps.html> (330 Q&As Dumps, **40%OFF Special Discount: Exam-Tests**)

NEW QUESTION: 77

Which Ethernet to Cisco Fabric Interconnect connectivity configuration is supported when FCoE is implemented?

- A. VSS that has unified uplinks
- B. Ethernet and unified ports on the same port channel
- C. vPC that has unified uplinks
- D. cross-connections with pinning

Answer: C (LEAVE A REPLY)

Section: Storage Network Design

Explanation

Explanation/Reference: <https://www.cisco.com/c/en/us/support/docs/servers-unified-computing/ucs-manager/116188-configure-fcoe-00.html#anc11>

NEW QUESTION: 78

What is a design consideration when implementing FSPF?

- A. Routes are based on the domain ID.
- B. Routes are based on the distance vector protocol.
- C. FSPF runs only on F Ports.
- D. FSPF runs on a per-chassis basis.

Answer: A (LEAVE A REPLY)

Section: Network Design

Explanation/Reference: https://www.cisco.com/c/en/us/td/docs/switches/datacenter/mds9000/sw/5_0/configuration/guides/fabric/nxos/cli_fabric/fspf.html

NEW QUESTION: 79

Drag and drop the feature descriptions from the left onto the correct UCS Fabric Interconnect modes on the right.

Answer:

NEW QUESTION: 80

A network architect designs a high-availability architecture for the Cisco UCS Fabric Interconnects that are installed in a data center. The architecture must support clustering and redundancy.

Which architecture meets these requirements?

- A. dual connections from port L1 to L1 and one connection from port L1 to L1 with twinax cables
- B. dual connections from port L1 to L2 and one connection from port L2 to L1 with twinax cables
- C. dual connections from port L1 to L2 and one connection from port L2 to L1 with Ethernet cables
- D. dual connections from port L1 to L1 and one connection from port L2 to L2 with Ethernet cables

Answer: D ([LEAVE A REPLY](#))

Reference:

ch10lv1sec92/configuring-high-availability-clustering

NEW QUESTION: 81

Drag and drop the feature descriptions from the left onto the correct UCS Fabric Interconnect modes on the right.

Answer:

NEW QUESTION: 82

Which authentication software natively runs within the CLI of Cisco NX-OS devices?

- A. Puppet
- B. Ansible
- C. Python
- D. Chef

Answer: B ([LEAVE A REPLY](#))

NEW QUESTION: 83

A customer needs to deploy a three-tier network architecture that will consist of web, app, and other businesscritical applications. The solution will include Cisco UCS 6324 Fabric Interconnects managing B and C series servers. The fabric interconnects will be connected to the Cisco Nexus 7706 Series Switch for network access.

A storage array will be directly connected to the UCS fabric interconnects.

Which UCS deployment type must be used to meet these requirements?

- A. UCS interconnect in Ethernet end-host mode
UCS interconnect in Fibre Channel end-host mode
Fabric Interconnects uplinked to the Nexus device using an LACP port-channel in passive mode
- B. UCS interconnect in Ethernet end-host mode
UCS interconnect in Fibre Channel switching mode
Fabric Interconnects uplinked to the Nexus device using an LACP port-channel in active mode
- C. UCS interconnect in Ethernet switching mode
UCS interconnect in Fibre Channel switching mode
Fabric Interconnects uplinked to the Nexus device using an LACP port-channel in passive mode

D. UCS interconnect in Ethernet switching mode

UCS interconnect in Fibre Channel end-host mode

Fabric Interconnects uplinked to the Nexus device using an LACP port-channel in active mode

Answer: ([SHOW ANSWER](#))

NEW QUESTION: 84

What are two reasons to select OTV as the DCI solution to connect multisite topologies? (Choose two.)

A. It propagates hosts reachability without support of traffic flooding.

B. Layer 3 failures do not propagate beyond the OTV edge device.

C. It extends the spanning tree between data centers.

D. It is an open standard.

E. It constrains HSRP hello messages to each data center.

Answer: **B,C** ([LEAVE A REPLY](#))

Section: Network Design

Explanation/Reference: https://www.cisco.com/c/en/us/td/docs/solutions/Enterprise/Data_Center/DCI/whitepaper/

DCI3_OTV_Intro/DCI_1.html

NEW QUESTION: 85

A network engineer is designing a Cisco Hyperflex infrastructure. The Infrastructure will be connected to an external SAN fiber channel array and must support Microsoft clustering.

Which storage connectivity method must be used to meet these requirements?

A. Internet Small Computer Systems Interface

B. Fibre Channel over Ethernet

C. raw device mapping

D. server message block

Answer: ([SHOW ANSWER](#))

Source is from Cisco Press Hyperconverged Infrastructure Data Centers: Demystifying HCI.

NEW QUESTION: 86

Which mode must be enabled on a Cisco UCS Fabric Interconnect to connect directly to a storage array?

A. NPIV mode

B. FC end-host mode

C. NPV mode

D. FC switching mode

Answer: **D** ([LEAVE A REPLY](#))

Explanation

Section: Storage Network Design

NEW QUESTION: 87

What influences the number of ISLs that are required between Cisco MDS Series switches?

A. type of storage

- B. end-to-end oversubscription ratio
- C. N Port virtualization
- D. FCoE protocol

Answer: ([SHOW ANSWER](#))

NEW QUESTION: 88

An engineer designs a Cisco UCS solution that must provide guaranteed and deterministic bandwidth to a specific server in the environment. The solution must apply to network and storage traffic of C-Series and B-Series servers. Which solution should be included to meet these requirements?

- A. Pin the server ports of the service profile to dedicated uplink ports.
- B. Pin the vNICs and the vHBAs of the service profile to dedicated uplink ports.
- C. Pin the IOM ports of the service profile to dedicated server ports.
- D. Pin the vNICs and vHBAs of the service profile to dedicated server ports

Answer: ([SHOW ANSWER](#))

Reference:

NEW QUESTION: 89

Drag and drop the Cisco Nexus 7000 Series Switch resources from the left onto the correct groups on the right.

Answer:

NEW QUESTION: 90

A confidentiality and integrity and it must be open standard. The solution must encrypt Ethernet frames regardless of the upper layer protocol used. Which technology must be used to support these requirements?

- A. GRE
- B. MACsec
- C. IPsec
- D. OTV

Answer: B ([LEAVE A REPLY](#))

The key to solution is "Ethernet frames". Frames are layer 2. IPsec encrypts at layer 3.

NEW QUESTION: 91

Which address pool is used when a vHBA template is created?

- A. UUID
- B. WWPN
- C. IP
- D. MAC

Answer: B ([LEAVE A REPLY](#))

Valid 300-610 Dumps shared by PrepPdf.com for Helping Passing 300-610 Exam! PrepPdf.com now offer the **newest 300-610 exam dumps**, the PrepPdf.com 300-610 exam **questions have been updated** and **answers have been corrected** get the **newest** PrepPdf.com 300-610 dumps with Test Engine here: <https://www.preppdf.com/Cisco/300-610-prepaway-exam-dumps.html> (330 Q&As Dumps, **40%OFF Special Discount: Exam-Tests**)

NEW QUESTION: 92

Drag the requirements from the left onto the correct policy types on the right.

Answer:

NEW QUESTION: 93

An engineer must secure the payload traversing across the DCI. The solution must support confidentiality and integrity and it must be open standard. The solution must encrypt Ethernet frames regardless of the upper layer protocol used. Which technology must be used to support these requirements?

- A. GRE
- B. MACsec
- C. IPsec
- D. OTV

Answer: B (LEAVE A REPLY)

The key to solution is "Ethernet frames". Frames are layer 2. IPsec encrypts at layer 3.

NEW QUESTION: 94

Which factor determines the choice of platform designing a Cisco HyperFlex infrastructure to support computer-aided design applications?

- A. network speed
- B. processor count
- C. GPU support
- D. storage capacity

Answer: D (LEAVE A REPLY)

NEW QUESTION: 95

What are two advantages of using Cisco vPC over traditional access layer designs? (Choose two.)

- A. supports Layer 3 port channels
- B. disables spanning-tree
- C. no spanning-tree blocked ports
- D. uses all available uplink bandwidth
- E. maintains single control plane

Answer: (SHOW ANSWER)

Section: Network Design

Explanation/Reference: https://www.cisco.com/c/dam/en/us/td/docs/switches/datacenter/sw/design/vpc_design/vpc_best_practices_design_guide.pdf

NEW QUESTION: 96

What are two advantages of using Cisco vPC as compared to traditional access layer designs? (Choose two.)

- A. disables spanning-tree
- B. no spanning-tree blocked ports
- C. uses all available uplink bandwidth
- D. maintains single control plane
- E. supports Layer 3 port channels

Answer: B,C ([LEAVE A REPLY](#))

NEW QUESTION: 97

Refer to the exhibit.

What must be the default gateway of the servers in EPG Web?

- A. subnet address of BD1
- B. subnet address of BD2
- C. subnet address of L3Out
- D. NAT appliance

Answer: D ([LEAVE A REPLY](#))

NEW QUESTION: 98

A network administrator must create a redundant vHBA for the mission-critical virtual machines (VMs) installed on a Cisco UCS Fabric Interconnect blade server. The VMs access multiple datastores using VSAN55 and VSAN95. The datastore on which the VMs are hosted must be accessible if any of the uplinks goes offline. Which action meets these requirements?

- A. Assign VSAN55 and VSAN95 to vHBA1 and vHBA2.
- B. Attach VSAN55 to vHBA1 and VSAN95 to vHBA2.
- C. Enable failover for the vHBA with VSAN55 and VSAN95 enabled.
- D. Configure load-balancing for vHBAs with VSAN55 and VSAN95 attached.

Answer: ([SHOW ANSWER](#))

NEW QUESTION: 99

An engineer must design a multitenant solution using Cisco 7709 switches. The solution must support separate routing instances, separate spanning tree domains, and separate firewalls for each tenant. Which solution meets these requirements?

- A. VRF
- B. VDC
- C. CFS
- D. vPC

Answer: B ([LEAVE A REPLY](#))

NEW QUESTION: 100

Which two configurations are available by using a service profile template in Cisco UCS Manager? (Choose two.)

- A. ARP entries

- B. UUID assignment
- C. target server
- D. number of vHBAs
- E. VXLAN membership

Answer: B,D ([LEAVE A REPLY](#))

NEW QUESTION: 101

The management of the Cisco Nexus switches is provided over an isolated out-of-band network. The VDC feature is configured on the Cisco Nexus core switches. How is out-of-band management access provided for each VDC?

- A. All the VDC have the same out-of-band IP address.
- B. Each VDC has a unique out-of-band IP address from the same IP subnet.
- C. Each VDC has a unique out-of-band IP address from different IP subnets among VDCs.
- D. Each VDC has a dedicated out-of-band Ethernet management port.

Answer: B ([LEAVE A REPLY](#))

NEW QUESTION: 102

Drag and drop the Cisco Nexus 7000 Series Switch resources from the left onto the correct groups on the right.

Answer:

NEW QUESTION: 103

Which two features are provided by deploying an OOB management network in a Cisco Nexus data center?

(Choose two.)

- A. Layer 3 path for monitoring purposes
- B. Layer 2 path for a vPC peer link
- C. Layer 3 path for server traffic
- D. Layer 2 path for server traffic
- E. Layer 3 path for vPC keepalive packets

Answer: B,D ([LEAVE A REPLY](#))

NEW QUESTION: 104

A failure occurs on the network between two BFD and OSPF neighbors. Drag and drop the protocol actions from the left into the correct order on the right.

Answer:

Explanation

NEW QUESTION: 105

Which Ethernet to Cisco Fabric Interconnect connectivity configuration is supported when FCoE is implemented?

- A. cross-connections with pinning
- B. vPC that has unified uplinks
- C. VSS that has unified uplinks

D. Ethernet and unified ports on the same port channel

Answer: B (LEAVE A REPLY)

NEW QUESTION: 106

A network architect proposes a distinct Fibre Channel fabric to be used for a Cisco UCS blade server that hosts critical applications. Which action should be implemented for the fibre Channel traffic from the vHBA of this service to pass through the I/O module in the Cisco chassis to a specified uplink Fibre Channel port?

A. Include a SAN pin group in the vHBA policy.

B. Update the applied Fibre Channel adapter policy.

C. Update the applied global QoS policy.

D. Enable persistent binding in the vHBA policy.

Answer: A (LEAVE A REPLY)

Reference:

https://www.cisco.com/c/en/us/td/docs/unified_computing/ucs/ucs-manager/GUI-User-Guides/Storage-Mgmt/3-2/b_UCSM_GUI_Storage_Management_Guide_3_2/b_UCSM_GUI_Storage_Management_Guide_3_2_chapter_0110.pdf

Valid 300-610 Dumps shared by PrepPdf.com for Helping Passing 300-610 Exam! PrepPdf.com now offer the **newest 300-610 exam dumps**, the PrepPdf.com 300-610 exam **questions have been updated** and **answers have been corrected** get the **newest** PrepPdf.com 300-610 dumps with Test Engine here: <https://www.preppdf.com/Cisco/300-610-prepaway-exam-dumps.html> (**330 Q&As Dumps, 40%OFF Special Discount: Exam-Tests**)

NEW QUESTION: 107

An engineer must connect an existing Cisco UCS Fabric Interconnect to an IP-based storage array. The connection must be a port channel made directly between the fabric interconnect expansion module and the storage array. The engineer must also consider that the environment is running FCoE for storage and uses QoS to prioritize traffic.

Which port type should be used to meet these requirements?

A. uplink

B. server

C. appliance

D. network

Answer: (SHOW ANSWER)

NEW QUESTION: 108

A customer requires a tool to manage Cisco network hardware. The solution must use secure communication using a secure network protocol, support the use of declarative language to manage the state of resources, and periodically pull changes to the controlled nodes. Which tool meets these requirements?

A. Nomir

B. Ansible

C. SaltStack

D. Puppet

Answer: ([SHOW ANSWER](#))

NEW QUESTION: 109

Drag and drop the feature descriptions from the left onto the correct UCS Fabric Interconnect modes on the right.

Answer:

NEW QUESTION: 110

Refer to the exhibit.

A high-availability setup for iSCSI is designed with the host running iSCSI software. Each storage port on the MDS exports the same two Fibre Channel target ports with different iSCSI target names. In this design, how many iSCSI sessions are created from the host so that recovery occurs if any component fails?

- A. 2
- B. 3
- C. 4
- D. 5

Answer: C ([LEAVE A REPLY](#))

https://www.cisco.com/en/US/docs/storage/san_switches/mds9000/sw/rel_3_x/configuration/guides/fm_3_2/ciscsi.html

Valid 300-610 Dumps shared by PrepPdf.com for Helping Passing 300-610 Exam! PrepPdf.com now offer the **newest 300-610 exam dumps**, the PrepPdf.com 300-610 exam **questions have been updated** and **answers have been corrected** get the **newest** PrepPdf.com 300-610 dumps with Test Engine here: <https://www.preppdf.com/Cisco/300-610-prepaway-exam-dumps.html> (330 Q&As Dumps, **40%OFF Special Discount: Exam-Tests**)