

Huawei.H12-261_V3.0-ENU.v2022-03-01.q114

Exam Code:	H12-261_V3.0-ENU
Exam Name:	HCIE-Routing & Switching (Written) V3.0
Certification Provider:	Huawei
Free Question Number:	114
Version:	v2022-03-01
# of views:	2386
# of Questions views:	1140
https://www.freeqas.com/qa/Huawei/H12-261_V3.0-ENU/Huawei.H12-261_V3.0-ENU.v2022-03-01.q114.html	

NEW QUESTION: 1

Regarding the BGP anti-ring mechanism, which of the following description is correct?
(Multiple Choice)

- A. Routes learned from IBGP are not advertised to IBGP neighbors to prevent routing loops within the AS.
- B. The Cluster List attribute is used for the anti-ring in the reflector cluster. If the router discovers that the cluster list of the route entry contains its own cluster ID, it will reject the route.
- C. You can use the AS_CONFED_SET attribute to prevent loops within the federation.
- D. Use the AS_PATH attribute between autonomous systems to prevent loops.

Answer: A,C,D (LEAVE A REPLY)

NEW QUESTION: 2

What kind of packets can Huawei equipment perform traffic suppression for? (Multiple Choice)

- A. Broadcast
- B. Multicast
- C. Unknown unicast
- D. Known unicast

Answer: A,B,C (LEAVE A REPLY)

NEW QUESTION: 3

An OSPF protocol is running on a company network. An engineer wants to understand the OSPF mechanism to perform packet capture operations on the network, which of the following description about the OSPF packet is correct? (Multiple Choice)

- A. Sending Hello packets immediately after the interface joins the OSPF area.

- B. The LS Update message is sent only when the adjacency is established.
- C. After receiving the LS Update message, the router must send LS Ack to confirm.
- D. LS Update message synchronizes the link state database by sending detailed LSA information.

Answer: [\(SHOW ANSWER\)](#)

NEW QUESTION: 4

In an MPLS VPN network, different CE devices can exchange routing information with the same PE device using different routing protocols. The routing protocols used between different CE devices and the same device are independent of each other.

- A. False
- B. True

Answer: **B** [\(LEAVE A REPLY\)](#)

NEW QUESTION: 5

After reset isis all is executed, the IS-IS protocol process needs to be restarted and neighbors need to be re-established, but various IS-IS statistics will not be cleared.

- A. FALSE
- B. TRUE

Answer: **A** [\(LEAVE A REPLY\)](#)

NEW QUESTION: 6

Which of the following is the correct description of the Register message in PIM-SM?
(Multiple choice)

- A. Register message enables the RP to learn multicast source information.
- B. Register message is sent by the source DR
- C. Register message is sent to the RP by unicast instead of multicast.
- D. Register message is sent by the receiver router

Answer: **A,B,C** [\(LEAVE A REPLY\)](#)

NEW QUESTION: 7

Which of the following descriptions are true about the establishment process of LDP LSP?
(Multiple Choice)

- A. In the label publishing DoD mode, for a specific FEC, the LSR does not need to obtain the label request message from the upstream to perform label distribution and distribution.
- B. The process of establishing an LSP is actually the process of binding the FEC to the label and advertising the binding to the upstream LSR of the LSP.
- C. When the network topology changes cause the next hop neighbor to change, the LSR can directly reestablish the LSP by using the label sent by the original non-optimal next hop neighbor.

D. By default, the LSR is for the same FEC. The received label mapping can only come from the optimal next hop. It cannot be from the non-optimal next hop.

Answer: A,B,C ([LEAVE A REPLY](#))

NEW QUESTION: 8

About BGP Union, which of the following description is wrong?

- A. Sub-autonomous systems in the alliance can use private AS numbers. For Huawei NE/AR routers, an alliance can configure up to 32 sub-autonomous systems.
- B. The alliance divides an AS into several sub-ASs, and the AS outside the alliance still considers the alliance to be an AS.
- C. Alliance sub AS number, other than the default notice to the Union BGP peers.
- D. Union can easily be detected AS routing loop inside, because the sub- AS operation is between the EBGP.

Answer: ([SHOW ANSWER](#))

NEW QUESTION: 9

Regarding the description of IGMP Snooping, which is correct? (Multiple Choice)

- A. IGMP Snooping does not consume the CPU of the switch
- B. IGMP Snooping runs at the link layer and is a multicast restriction mechanism on the Layer 2 Ethernet switch, which is used to manage and control multicast groups
- C. IGMP Snooping builds a MAC multicast address table by monitoring IGMP messages sent by the host
- D. IGMP Snooping solves the problem of multicast packets broadcast at Layer 3

Answer: B,C ([LEAVE A REPLY](#))

NEW QUESTION: 10

ISIS IPv6 cost 50 is configured on the interface. What is the meaning of this command?

- A. IS-IS of the interface
- B. The IS-IS cost of the interface is both 50 and the cost is both 60

Answer: A ([LEAVE A REPLY](#))

NEW QUESTION: 11

After the BGP route is imported to other protocols, the next hop in the BGP routing table is the same as the next hop of the routing protocol imported.

- A. False
- B. True

Answer: A ([LEAVE A REPLY](#))

NEW QUESTION: 12

Configure queue-based traffic shaping. If the queue length exceeds the cache size, the tail is discarded by default.

A. False

B. True

Answer: A ([LEAVE A REPLY](#))

NEW QUESTION: 13

In an MPLS domain, LSRs can be divided into Ingress LSR, Transit LSR, and Egress LSR according to the way of LSR processing data. For the same FEC. A certain LSR may also be the Ingress LSR of the FEC or the transit LSR of the FEC.

A. FALSE

B. TRUE

Answer: A ([LEAVE A REPLY](#))

NEW QUESTION: 14

Which of the following is wrong about HTTPS?

A. If the HTTPS traffic contains a virus, the router cannot directly detect the virus using IPS technology.

B. When using HTTPS to access a website, if the user's browser does not recognize the digital certificate of the website, the website cannot be accessed.

C. HTTPS protocol uses TCP port 443 by default.

D. HTTPS secures access to data by using SSL VPN.

Answer: ([SHOW ANSWER](#))

NEW QUESTION: 15

BGP 4+ runs between the two routers. The neighbor relationship is normal. However, the BGP routing table of the local router does not have neighbor's routing entry. What is the possible reason? (Multiple Choice)

A. Peer ignore configured on the peer

B. The next hop address of the BGP routing entry is unreachable.

C. The routing entries of the peer BGP routing table are non-optimal.

D. Active-route-advertise configured on the peer

Answer: B,C,D ([LEAVE A REPLY](#))

NEW QUESTION: 16

The filter policy 2000 export is configured in the IS-IS process. Which of the following is wrong about the function of this command?

A. This command will filter the link state information released to the outside world

B. The routing entries generated by the device itself will be restricted from being released to the outside world

C. If this command is not configured, the device will advertise all the routes imported by external routing protocols into IS-IS by default.

D. It needs to be used in conjunction with route import, which is used to advertise only part of the imported external routes to neighbors.

Answer: B (LEAVE A REPLY)

Valid H12-261_V3.0-ENU Dumps shared by PrepPdf.com for Helping Passing H12-261_V3.0-ENU Exam! PrepPdf.com now offer the **newest H12-261_V3.0-ENU exam dumps**, the PrepPdf.com H12-261_V3.0-ENU exam **questions have been updated** and **answers have been corrected** get the **newest** PrepPdf.com H12-261_V3.0-ENU dumps with Test Engine here:

https://www.preppdf.com/Huawei/H12-261_V3.0-ENU-prepaway-exam-dumps.html

(485 Q&As Dumps, **40%OFF Special Discount: Exam-Tests**)

NEW QUESTION: 17

In a basic network layer data packet, which of the following information can be included?
(Multiple choice)

- A. Network layer header
- B. Upper-level data
- C. Data link layer header
- D. Network layer tail

Answer: A,B (LEAVE A REPLY)

NEW QUESTION: 18

What is the three-layer logical interface used to implement different VXLAN virtual network communication on the VXLAN L3 Gateway?

- A. NVE interface
- B. VI ANIF interface
- C. Layer 2 sub-interface
- D. VBDIF interface

Answer: (SHOW ANSWER)

NEW QUESTION: 19

If the OSPF protocol is running on the network, configure the non-backbone area in the OSPF area as the LSA with the ls-id of 0.0.0.0 in the Totally Stub Totally Stub area. Which LSA does the LSA belong to?

- A. LSA5
- B. LSA1
- C. LSA2
- D. LSA3

Answer: (SHOW ANSWER)

NEW QUESTION: 20

The correct description in the following of BGP loop protection is: (Multiple Choice)

- A. DBGP routers will not announce any updates from EBGP peers to their EBGP peers
- B. Non-RR BGP routers will not announce any update information from IBGP peers to other IBGP peers
- C. Through the AS-PATH attribute, discard any update information received from EBGP peers that contains its own AS number in the AS-PATH attribute
- D. Any routing information from IBGP peers will be advertised to other IBGP peers

Answer: B,C ([LEAVE A REPLY](#))

NEW QUESTION: 21

In an MPLS BGP VPN network that does not enable the MPLS penultimate hop pop-up technology, when the message reaches the last hop PE, the message has two layers of labels, and the two layers of label values can be the same.

- A. TURE
- B. FALSE

Answer: A ([LEAVE A REPLY](#))

NEW QUESTION: 22

Which of the following description about OSPFV3 protocol authentication is wrong?

- A. Huawei router OSPFv3 IPsec certification can not only support transmission mode, but also support tunnel mode
- B. OSPFV3 can only use manual mode to establish SA
- C. An OSPFv3 protocol header is removed Autype and Authentication field
- D. OSPFV3 authentication relies on the authentication header and encapsulation security payload header of IPv6 packets

Answer: ([SHOW ANSWER](#))

NEW QUESTION: 23

Regarding BGP/MPLS IP VPN routing interaction, which is wrong in the following description?.

- A. The egress PE can send IPv4 routes to the remote CE through BGP, IGP or static routing
- B. After the egress PE receives the VPNv4 route advertised by the ingress PE, it filters the VPNv4 route according to the RT attribute carried by the route
- C. The exchange between PE and CE is IPv4 routing information
- D. The ingress PE will convert the IPv4 route received from the CE into a VPNv4 route, and save it according to different VPN instances

Answer: ([SHOW ANSWER](#))

NEW QUESTION: 24

Single selection After configuring the VLAN-based MAC address drift detection function, if the MAC address drifts, you can configure the actions of the interface according to your needs.

Which of the following is not a configurable action?

- A. MAC address blocking
- B. Send alert
- C. Flow filtering
- D. Interface blocking

Answer: C ([LEAVE A REPLY](#))

NEW QUESTION: 25

Which of the following statements about IS-IS Hello packets are correct? (Multiple choice)

- A. Level-1 LAN IIH does not contain System ID
- B. Level-1 LAN IH is sent by multicast
- C. P2P IH has no Priority field
- D. P2P IIH and LAN IIH are exactly the same

Answer: ([SHOW ANSWER](#))

NEW QUESTION: 26

What is the main reason why RSTP converges faster than STP?

- A. RSTP has less overhead
- B. RSTP is not based on timer convergence
- C. RSTP increases the type of port status
- D. RSTP has a smaller timer

Answer: B ([LEAVE A REPLY](#))

NEW QUESTION: 27

The router HW1 exists as an MPLS LSR router in the network of the operator HW. The router receives a packet carrying a label, but the label entry does not exist in its LFIB.

So how does the router handle the message?

- A. Router HW1 uses LDP to create an LSP and creates a new path for the label carried in the packet in the LFIB.
- B. Router HW1 will strip the label and find the IP destination address of the FIB.
- C. Router HW1 will discard the message.
- D. Router HW1 will forward the message using the default label.

Answer: C ([LEAVE A REPLY](#))

NEW QUESTION: 28

Which of the following statements about VXLAN messages is correct? (Multiple choice)

- A. The source UDP port number is 4789

- B. VNI has 24 bits and is used to distinguish VLAN segments.
- C. The outer destination IP address is the IP address of the remote VTEP of the VXLAN tunnel.
- D. Destination UDP port number is 4789

Answer: B,C,D (LEAVE A REPLY)

NEW QUESTION: 29

What are the comparison items of the main switch election in the stack? (Multiple questions)

- A. Stack ID
- B. MAC address
- C. Running status
- D. Stacking priority

Answer: B,C,D (LEAVE A REPLY)

NEW QUESTION: 30

For Layer 2 VPN technology, which of the following statements are correct? (Multiple Choice)

- A. BGP EVPN solves the problem of MAC address drift and multi-tenancy that VPLS cannot support.
- B. BGP EVPN supports tenant isolation, multi-homing and broadcast suppression
- C. The VPLS configuration is highly complex. The Layer 2 network transparently transmits BUM packets.
- D. VPLS is a widely used technology on the live network. It can provide Layer 3 packet transparent transmission and achieve multi-point access.

Answer: A,B,C (LEAVE A REPLY)

NEW QUESTION: 31

Enable SSM on the entire IP multicast network.

Which of the following statements about SSM are correct? (Multiple Choice)

- A. SSM is suitable for one-to-many application
- B. Only SPT is used for SSM.
- C. SSM is recommended when there are multiple sources on the network and multicast routing is simple.
- D. No RP is required.
- E. Only RPT is used for SSM.

Answer: A,B,D (LEAVE A REPLY)

Valid H12-261_V3.0-ENU Dumps shared by PrepPdf.com for Helping Passing H12-261_V3.0-ENU Exam! PrepPdf.com now offer the **newest H12-261_V3.0-ENU exam dumps**, the PrepPdf.com H12-261_V3.0-ENU exam **questions have been updated** and **answers have been corrected** get the **newest** PrepPdf.com H12-261_V3.0-ENU dumps with Test Engine here:
https://www.preppdf.com/Huawei/H12-261_V3.0-ENU-prepaway-exam-dumps.html
(485 Q&As Dumps, **40%OFF Special Discount: Exam-Tests**)

NEW QUESTION: 32

Which AS_PATH can the command ip as-path-filter1 permit^12*74\$ match?

- A. AS PATH (1236217432374)
- B. AS PATH (1253287423)
- C. AS PATH (321122374)
- D. AS PATH (32127423)

Answer: A (LEAVE A REPLY)

NEW QUESTION: 33

Which version of the VRRP protocol is correct? (Multiple questions)

- A. VRRPv2 is only applicable to IPv4
- B. VRRPv3 is only applicable to IPv6
- C. VRRPv3 does not support authentication
- D. VRRPv2 supports authentication

Answer: (SHOW ANSWER)

NEW QUESTION: 34

The attacker responds to the request by sending ICMP and sets the destination address of the request packet to the broadcast address of the victim network to achieve the purpose of the attack.

So what kind of attack does this behavior belong to?

- A. IP spoofing attack
- B. Smurf attack
- C. ICMP redirect attack
- D. SYN flood attack

Answer: B (LEAVE A REPLY)

NEW QUESTION: 35

An existing BGP router HW1 is configured with both an IBGP neighbor and an EBGP neighbor.

Which of the following descriptions are correct about IBGP neighbors and EBGP neighbors? (Multiple Choice)

- A. The router will send BGP updates learned from its IBGP neighbors to its own other IBGP neighbors and EBGP neighbors.
- B. IBGP neighbors can establish neighbor relationships through loopback interfaces.
- C. The router will send BGP updates learned from its EBGP neighbors to its own other IBGP neighbors and EBGP neighbors.
- D. IBGP neighbors must be directly connected. Otherwise, IBGP-Multi-hop must be configured
- E. EBGP neighbors must establish neighbor relationships through directly connected physical interface addresses.
- F. EBGP neighbors must be directly connected. Otherwise, EBGP-Multi-hop must be configured

Answer: ([SHOW ANSWER](#))

NEW QUESTION: 36

What parameters can the DHCPv6 server assign to the DHCPv6 client? (Multiple choice)

- A. SNTP server address
- B. DNS server address
- C. IPv6 address prefix
- D. Gateway address

Answer: A,B,C ([LEAVE A REPLY](#))

NEW QUESTION: 37

The following procedure for NDP to resolve the link layer address is correct or not.

- A. False
- B. True

Answer: A ([LEAVE A REPLY](#))

NEW QUESTION: 38

RTA is the source DR router and RTB is the RP router. The multicast source sends multicast data to RTA, but the multicast source Source registered to it through the PIM Register message cannot be seen on RTB. What are the possible reasons? (Multiple questions)

- A. The multicast network dynamically elects the RP, but the RTA's RPF check on the BSR fails
- B. The RP elected by RTA is not RTB
- C. The multicast network is statically configured with RP, but the RTA router is not statically configured with RP
- D. There is no unicast route from RTB to RTA, causing RTB to fail to check the source RPF

Answer: A,B,C,D ([LEAVE A REPLY](#))

NEW QUESTION: 39

The interface Serial0 of an existing router is in OSPF area 1, and the interface Serial0 is set to the Silent interface, so what effect does this setting have?

- A. OSPF does not add routes learned from the interface to the local routing table.
- B. OSPF does not establish any adjacencies through the interface.
- C. OSPF will receive routing updates from neighbors
- D. OSPF establishes available adjacencies through this interface.

Answer: B (LEAVE A REPLY)

NEW QUESTION: 40

What is the relationship between CIR, BC and TC?

- A. $CIR = BE/TC$
- B. $TC = CIR/BC$
- C. $TC = BC/CIR$
- D. $CIR = TC/BC$

Answer: C (LEAVE A REPLY)

NEW QUESTION: 41

Which of the following statements about URPF, IPSG and DAI are wrong? (Multiple Choice)

- A. URPF can be used to prevent DDoS false source attacks.
- B. IPSG checks the source IP address and MAC address of the IP message. DAI only checks the correspondence between IP and MAC.
- C. DAI does not support manual configuration of the binding table.
- D. IPSG technology checks IP packets to prevent source IP spoofing attacks, while DAI checks ARP packets to filter the attack source

Answer: B,C (LEAVE A REPLY)

NEW QUESTION: 42

There is an AS-path-filter, ip as-path-filter 1 permit ^100(_100)*(_400)*, which AS-PATH attribute cannot be matched by the As-path-filter?

- A. 100
- B. 100 400
- C. 100 200 900
- D. 100 400 400 400

Answer: C (LEAVE A REPLY)

NEW QUESTION: 43

As shown in the figure, in the IPv4 and IPv6 environment, the SEL field in the ISIS NET address always takes the value 00.

- A. True

B. False

Answer: A ([LEAVE A REPLY](#))

NEW QUESTION: 44

Which of the following statement about the digital certificate is wrong?

- A. Even if the two PRI entities are not in the same CA system, the two parties can complete the authentication as long as they can identify each other.
- B. When the received peer certificate is valid, but the device itself is in the wrong time and is not within the validity period of the certificate, the authentication fails.
- C. The digital certificate contains public key information.
- D. Digital signatures guarantee the integrity of digital certificates.

Answer: A ([LEAVE A REPLY](#))

NEW QUESTION: 45

As shown in the figure, the MP-BGP neighbor relationship is established between PE1 and PE2 through Loopback 0 interface. After the configuration is completed, it is found that CE1 and CE2 cannot learn the path from each other. Which of the following options will cause this problem? (Multiple choice)

- A. The LSP tunnel between PE1 and PE2 is not established
- B. PE1 or PE2 is not enabled with neighbors in BGP-VPNv4 unicast address family view
- C. The routing protocol configuration between PE1 or PE2 and the respective CE is incorrect
- D. The VPN instance parameter configuration on PE1 or PE2 is incorrect

Answer: A,B,C,D ([LEAVE A REPLY](#))

NEW QUESTION: 46

The SWA and SWB are connected by two physical Ethernet links.

The SWA has the following interface configurations:

```
[SWA]interface GigabitEthernet 1/0/1
```

```
[SWA-GigabitEthernet 1/0/1] port link-type trunk
```

```
[SWA-GigabitEthernet 1/0/1] port trunk allow-pass vlan 1 0 100
```

```
[SWA]interface GigabitEthernet 1/0/2
```

131 / 144 The safer , easier way to help you pass any IT exams.

```
[SWA-GigabitEthernet 1/0/2] port link-type trunk
```

```
[SWA-GigabitEthernet 1/0/2] port trunk allow-pass vlan 1 10
```

These two links are aggregated

Assume that the configuration on the SWB is correct.

Which of the following statements are correct in view of this information? (Multiple Choice)

- A. GigabitEthernet 1/0/1 and GigabitEthernet 1/0/2 can be added to the same LAG without changing the current configuration.

- B.** GigabitEthernet 1/0/1 and GigabitEthernet 1/0/2 cannot be added to the same LAG because the allowed VLANs are different.
- C.** GigabitEthernet 1/0/1 and GigabitEthernet 1/0/2 can be added to the same LAG only after GigabitEthernet 1/0/2 is configured. Change to the same as GigabitEthernet 1/0/1
- D.** After the link aggregation is configured on the SWA and the SWB, if enabled MSTP, GigabitEthernet 1/0/1 and GigabitEthernet 1/0/2 will enter the Forwarding state in MSTP

Answer: B,C (LEAVE A REPLY)

Valid H12-261_V3.0-ENU Dumps shared by PrepPdf.com for Helping Passing H12-261_V3.0-ENU Exam! PrepPdf.com now offer the **newest H12-261_V3.0-ENU exam dumps**, the PrepPdf.com H12-261_V3.0-ENU exam **questions have been updated** and **answers have been corrected** get the **newest** PrepPdf.com H12-261_V3.0-ENU dumps with Test Engine here:

https://www.preppdf.com/Huawei/H12-261_V3.0-ENU-prepaway-exam-dumps.html

(485 Q&As Dumps, **40%OFF Special Discount: Exam-Tests**)

NEW QUESTION: 47

Regarding the configuration of the security level of the firewall security zone, which of the following statement is wrong?

- A.** Once the security level is set, it is not allowed to change
- B.** The newly created security zone, the system defaults its security level to 1
- C.** In the same system, two security zones are not allowed to configure the same security level
- D.** The security level can only be set for the custom security zone

Answer: B (LEAVE A REPLY)

NEW QUESTION: 48

Regarding the stub area and NSSA area of the OSPF protocol, which of the following statements are wrong?

- A.** Type5 LSA is not allowed to be injected in the stub area, but it is allowed to be injected in the NSSA area
- B.** Type3 LSA injection is allowed to be injected in both stub area and NSSA area
- C.** Type7 LSA is not allowed to be injected in the stub area, but it is allowed to be injected in the NSSA area
- D.** Type4 LSA is not allowed to be injected into both stub areas and NSSA areas

Answer: A (LEAVE A REPLY)

NEW QUESTION: 49

As shown in the following picture, which of the following description is correct?

- A. R1 exist LSDB of Level-1 and Level-2 at the same time
- B. R1 has a route to R2 1oopback0 10.0.2.2/32
- C. No neighbor relationship can be established between R1 and R2.
- D. R1 may Ping through R21 1oopbak0 interface address

Answer: B (LEAVE A REPLY)

NEW QUESTION: 50

The security zones provided by Huawei firewall by default are: (Multiple Choice)

- A. Security zone
- B. Trust zone
- C. Local zone
- D. Untrust zone

Answer: B,C,D (LEAVE A REPLY)

NEW QUESTION: 51

In the ISIS broadcast network database synchronization process, the following statement which is correct?

- A. R1 and R3 maintain database consistency by periodically sending PSNP requests.
- B. R2 acts as DIS and periodically sends CSNP.
- C. R2 acts as DIS, and the Hello time is three times than the ordinary router.
- D. R2 acts as DIS will not receive PSNP requests for other routes.

Answer: B (LEAVE A REPLY)

NEW QUESTION: 52

SSH uses asymmetric encryption algorithms AES and DES to realize the security of data transmission, and uses HMAC to ensure the integrity of the data.

- A. TRUE
- B. FALSE

Answer: (SHOW ANSWER)

NEW QUESTION: 53

Which of the following tools cannot be directly referenced by the If-match clause in the Route-policy?

- A. AS-path-filter
- B. Regular expression
- C. Community-filt
- D. IP-prefix

Answer: B (LEAVE A REPLY)

NEW QUESTION: 54

Which of the following statements about the description of the firewall security zone is correct?

- A. The same interface of the firewall can belong to different security zones
- B. The built-in security zone of the firewall can be deleted
- C. Different interfaces of the firewall can belong to the same security zone
- D. Different security zones of the firewall can have the same priority

Answer: C ([LEAVE A REPLY](#))

NEW QUESTION: 55

The following statement about the security confederation SA in IPsec, which is wrong?

- A. The SA is uniquely identified by a triplet that includes the Security Parameter Index (SPI), the source IP address and the security protocol number used (AH or ESP).
- B. IPsec only supports the use of symmetric encryption algorithms to encrypt data.
- C. There must be two-way SA between IPsec peers to establish an IPsec VPN connection.
- D. Use display IPsec to view information about encryption algorithms, traffic, and other information used between another IPsec peer.

Answer: ([SHOW ANSWER](#))

NEW QUESTION: 56

In PIM-SM, which of the following descriptions of the PIM Join message is correct?

- A. The PIM Join message is sent every 60 seconds to refresh the status of the upstream router mroute for the multicast tree
- B. The upstream router sends a PIM Join confirmation in response to each PIM Join message received from the downstream router
- C. The PIM Join message is only sent when the multicast tree is established for the first time
- D. The PIM Join message is sent every 3 minutes to show the status of the new upstream router mroute for the multicast tree

Answer: ([SHOW ANSWER](#))

NEW QUESTION: 57

ISIS protocol is in broadcast network and P2P network, when the router receives the LSP, it needs to use PSNP to confirm and ensure the synchronization of the LSDB.

- A. False
- B. True

Answer: A ([LEAVE A REPLY](#))

NEW QUESTION: 58

What is the correct statement about the difference between OSPFv2 and OSPFv3?
(Multiple Choice)

- A. The protocol number of OSPFv2 in the IPv4 packet header is 89, and the next header number of OSPFv3 in the IPv6 packet header is 89
- B. OSPFv2 and OSPFv3 have the same types of messages: Hello, DD, LSR, LSU, LSA ack, and their message formats are the same
- C. OSPFv3 is similar to OSPFv2 in that it uses a multicast address as the destination address of OSPF packets
- D. Both OSPFv2 and OSPFv3 support interface authentication, and OSPFv3 authentication is still implemented based on the fields in the OSPF message header

Answer: A,B,C ([LEAVE A REPLY](#))

NEW QUESTION: 59

An existing router running OSPF is connected to Zone 0 and Zone 1. You configure zone 1 as a stub area. What types of LSA are only operating inside Zone 1?

- A. Type 7 LSA
- B. Type 1 LSA, Type 2 LSA and Type 5 LSA
- C. Type 1 LSA and Type 2 LSA
- D. Type 3 LSA and Type 4 LSA
- E. Type 1 LSA, Type 2 LSA and Type 3 LSA

Answer: ([SHOW ANSWER](#))

NEW QUESTION: 60

As shown in the figure, the ISIS overload bit is set in the configuration of router R3. Which of the following statements is correct? (Multiple Choice)

- A. The routes imported by R3 through import-route will not be advertised.
- B. R3 starts the load discussion state, R1 and R2 will not calculate the LSP generated by R3 in the SP tree.
- C. When the router memory is insufficient, the system automatically sets the overload flag in the sent LSP message, regardless of whether the user has configured the set-overload command.
- D. The direct route of R3 will be ignored by R1 and R2 because of the overload bit setting.
- E. The LSP of R3 will not spread to R1 and R2.

Answer: B,C ([LEAVE A REPLY](#))

NEW QUESTION: 61

In the packet forwarding of the cross-domain VPN-Option B mode, the two ASBRs will exchange the LSP labels of the public network once.

- A. False
- B. True

Answer: ([SHOW ANSWER](#))

Valid H12-261_V3.0-ENU Dumps shared by PrepPdf.com for Helping Passing H12-261_V3.0-ENU Exam! PrepPdf.com now offer the **newest H12-261_V3.0-ENU exam dumps**, the PrepPdf.com H12-261_V3.0-ENU exam **questions have been updated** and **answers have been corrected** get the **newest** PrepPdf.com H12-261_V3.0-ENU dumps with Test Engine here:
https://www.preppdf.com/Huawei/H12-261_V3.0-ENU-prepaway-exam-dumps.html
(485 Q&As Dumps, **40%OFF Special Discount: Exam-Tests**)

NEW QUESTION: 62

Command ip ip-prefix ip-prefix-name [index indexnumber{permit|deny}ipv4-address mask-length if a prefix list of less-equst has been specified, but greater-equal is not specified, then what is the scope of the prefix?

- A. [0 , less-equal-value]
- B. [mask-lenath , less-equal-value]
- C. No limit
- D. [ess-equal-value , 32]

Answer: (SHOW ANSWER)

NEW QUESTION: 63

Which of the following are the advantages of VLAN aggregation? (Multiple Choice)

- A. Reduce the waste of IP addresses
- B. Increase the number of available VLANs
- C. Realize the isolation of broadcast domains between Sub-VLANs
- D. Increase flexibility of addressing

Answer: A,B,C,D (LEAVE A REPLY)

NEW QUESTION: 64

Which property subject to the following two conditions?

- (1) BGP router A can choose whether to carry this attribute in the Update message.
- (2) if the router B receives the packet's attribute Update packet, router B cannot recognize the property, but will also contain the property Update message is advertised by the curved path to c router c possible to identify and use The attribute. (Multiple choice)

- A. Community
- B. Aggregator
- C. laocl_Pref
- D. Mult_Exit_Disc

Answer: A,B (LEAVE A REPLY)

NEW QUESTION: 65

The following is the description of the characteristics of the cross domain vpn-Option C, which is correct? (Multiple Choice)

- A. The VPN route is directly exchanged between the ingress PE and the egress PE, and no intermediate device is required to save and advertise the VPN route.
- B. Cross-domain VPN-Option-c mode is not suitable for use when spanning multiple AS.
- C. VPNv4 routes are not saved on the ASBR, and VPNv4 routes are not advertised to each other.
- D. Up to two layers of labels need to be used in the packet forwarding process.

Answer: A,C (LEAVE A REPLY)

NEW QUESTION: 66

Which of the following scenarios is not suitable for deploying interface policy routing?

- A. Modify the next hop of locally originated traffic
- B. On the core switch, draw the traffic from the internal network and external network to the AC device that is connected to the bypass
- C. In the scenario of multiple ISP outlets in the corporate network, different network segments of the intranet access the Internet through different ISP outlets
- D. On the core switch, the traffic of mutual access between the internal network and the external network is dragged to the side-mounted security detection device

Answer: A (LEAVE A REPLY)

NEW QUESTION: 67

A total of 6 bits indicating the priority field in the VLAN (802.1Q) data encapsulation

- A. False
- B. True

Answer: A (LEAVE A REPLY)

NEW QUESTION: 68

The second-layer network architecture of a company is as shown in the figure. After the engineer is configured, the services between the departments cannot be communicated. Check the status of the device as follows. Which is the possible reason?

- A. Instance VLAN mapping configuration between the switches is inconsistent
- B. The Revision Level configuration between switches is inconsistent
- C. The BPDU interval configuration between switches is inconsistent.
- D. The Region Name configuration between the switches is inconsistent

Answer: A,C,D (LEAVE A REPLY)

NEW QUESTION: 69

The rules of RR advertising routes break the rules of IBGP split horizon, so it may cause loops in the AS. What routing attributes does RR use to prevent loops? (Multiple choice)

- A. Originator ID

- B. Cluster List
- C. AS-PATH
- D. Nexthop

Answer: A,B ([LEAVE A REPLY](#))

NEW QUESTION: 70

The following description of the BSR mechanism, which is correct? (Multiple Choice)

- A. One C-BSR can also collect C-RP information through received C-RP packets.
- B. There can be multiple C-BSR in a PIM-SM domain, but only one BSR can be elected.
- C. The BSR collects C-RP information through the received C-RP data packets.
- D. The BSR advertises BSR information and C-RP information to all routers in the PIM-SM domain by flooding Bootstrap packets.

Answer: ([SHOW ANSWER](#))

NEW QUESTION: 71

Man-in-the-middle attacks or IP/MAC spoofing attacks can cause information leakage and other hazards, and are more common in intranets.

In order to prevent man-in-the-middle attacks or IP/MAC spoofing attacks, what configuration methods can be adopted?

- A. Configure the linkage between DHCP Snooping and DAI or IPSG on the switch
- B. Configure Trusted/Untrusted interface
- C. Limit the maximum number of MAC addresses that can be learned on the switch interface
- D. Enable DHCP Snooping to check the CHAD DR field in the DHCP REQUEST message

Answer: A ([LEAVE A REPLY](#))

NEW QUESTION: 72

In addition to stateless address autoconfiguration, IPv6 devices can also obtain information such as addresses, gateways, and DNS through DHCPv6.

- A. True
- B. False

Answer: B ([LEAVE A REPLY](#))

NEW QUESTION: 73

There is the concept of FEC-Forwarding Equivalence Class in MPLS, so on which of the following standards cannot FEC be allocated based?

- A. Class of Service
- B. Application Protocol
- C. Fragment offset
- D. Destination Address

Answer: C ([LEAVE A REPLY](#))

NEW QUESTION: 74

When the IPv6 address of the host is configured using stateless address configuration, and other parameters other than the address are obtained through DHCPv6, how should the M and O bits in the RA message be set?

- A. M=0 O=0
- B. M=0 O=1
- C. M=1 O=0
- D. M=1 O=1

Answer: B (LEAVE A REPLY)

NEW QUESTION: 75

When there are multiple redundant links in an IS-IS network, multiple equal-cost routes may appear.

Regarding equal-cost routes in an IS-IS network, which of the following descriptions is wrong?

- A. If load sharing is configured, the traffic will be evenly distributed to each link
- B. When the number of equal-cost routes in the networking is greater than the number configured through commands, and the priorities of these routes are the same, the route with the higher System ID of the next hop device is preferred for load sharing
- C. For each route in the equal-cost route, the priority can be specified, the route with the higher priority will be preferred, and the rest will be used as backup routes
- D. After the equal-cost routing priority is configured, when the IS-IS device forwards the traffic to the destination network segment, it will not adopt the load sharing method, but will forward the traffic to the next hop with the highest priority.

Answer: B (LEAVE A REPLY)

NEW QUESTION: 76

When the ABR is NSSA region of the 5/7 type LSA when changing dedicated router, then the ABR can 7 classes LSA converted from 5 classes LSA polymerization.

- A. True
- B. False

Answer: A (LEAVE A REPLY)

Valid H12-261_V3.0-ENU Dumps shared by PrepPdf.com for Helping Passing H12-261_V3.0-ENU Exam! PrepPdf.com now offer the **newest H12-261_V3.0-ENU exam dumps**, the PrepPdf.com H12-261_V3.0-ENU exam **questions have been updated** and **answers have been corrected** get the **newest** PrepPdf.com H12-261_V3.0-ENU dumps with Test Engine here:

NEW QUESTION: 77

ping -a X -c Y -s Z -vpn-instance M 10.5.2, what is the meaning of this command? (Multiple choice)

- A. The ping packet belongs to VPN instance M
- B. The ping sends Y ICMP requests
- C. The ICMP request of the ping, the packet size is Z (excluding IP and ICMP header)
- D. The source IP address of the ping packet is X

Answer: [\(SHOW ANSWER\)](#)

NEW QUESTION: 78

Huawei's SDN controllers using VXLAN technology is _____.

- A. Agile Controller-DCN
- B. Agile Controller-Campus
- C. Agile Controller-WAN

Answer: [A \(LEAVE A REPLY\)](#)

NEW QUESTION: 79

Which of the following are the advantages of using stacking and clustering technology to build a campus network? (Multiple choice)

- A. Business interruption time is greatly reduced
- B. Improved network equipment and link utilization
- C. Can effectively reduce network power consumption
- D. Simplifies network management and reduces the complexity of network deployment planning

Answer: [A,B,D \(LEAVE A REPLY\)](#)

NEW QUESTION: 80

If the router only needs to forward IPv6 packets, there is no need to configure any IPv4 protocols and addresses on the router.

- A. True
- B. False

Answer: [A \(LEAVE A REPLY\)](#)

NEW QUESTION: 81

How does the IGMPv2 router maintain the network segment group membership? (Multiple choice)

- A. The router maintains a timeout timer for each group membership, refreshes the timer if it receives the receiver host, and deletes the group membership if the timer expires

- B. After receiving the leave message, the router immediately deletes the group membership
- C. The router periodically sends Query messages. The receiver host reports the Report message after receiving the Query message.
- D. The router will query a specific group

Answer: C,D ([LEAVE A REPLY](#))

NEW QUESTION: 82

BGP can only auto-aggregate routes whose source is Incomplete.

- A. True
- B. False

Answer: A ([LEAVE A REPLY](#))

NEW QUESTION: 83

The LAND attack is performed by the attacker sending a source address and a destination address to the destination host are the destination host, the same SYN packet on source port and the destination port. When the receiver waits for the final ACK packet from the sender, the connection is always in a semi-connected state, resulting in waste of limited TCP resources at the receiving end.

- A. False
- B. True

Answer: ([SHOW ANSWER](#))

NEW QUESTION: 84

Which of the following statement about the LSA of OSPFv3 3 is correct? (Multiple choice)

- A. Router-LSA and Network-LSA do not contain routing information.
- B. Inter-Area-Prefix LSA also contains Link-Local information
- C. The Link State id of the Inter-Area Prefix-LSA contains the prefix information.
- D. When the Intra-Area Prefix LSA has the Referenced Link State Type-2, the Referenced Link State id contains the interface id of the DR.

Answer: A,D ([LEAVE A REPLY](#))

NEW QUESTION: 85

What is the command to configure VRRP preemption delay?

- A. vrrp vrid 1 preempt-timer 20
- B. vrrp vrid 1 preempt-delay 20
- C. vrrp vrid 1 timer delay 20
- D. vrrp vrid 1 preempt-mode timer delay 20

Answer: ([SHOW ANSWER](#))

NEW QUESTION: 86

Which of the following expressions can only match BGP routing entries that pass through AS200 and then AS300?

- A. `_(200 300)_`
- B. `^200 | ^300`
- C. `200$ | 300$`
- D. `_[200 300]_`

Answer: D (LEAVE A REPLY)

NEW QUESTION: 87

Which of the following is not the role of EVPN Type2 routing?

- A. Host MAC address Announcement
- B. Host ARP Announcement
- C. Host IP route Announcement
- D. BUM message forwarding

Answer: D (LEAVE A REPLY)

NEW QUESTION: 88

OSPFv2 is an IGP running on an IPv4 network; OSPFv3 is an IGP running on an IPv6 network. Compared with OSPFv2, OSPFv3 has a similar LSA type, but the functions are slightly different.

Which of the following is not included in the LSA type of OSPFv3?

- A. Router-LSA
- B. Network-LSA Router-LSA Network-LSA Inter-Area-Prefix-LSA Inter-Area-Router-LSA AS-External-LSA Group-membership-LSA Type-7-LSA Link-LSA Intra-Area-Prefix-LSA
- C. ASBR-Summary-LSA
- D. AS-External-LSA

Answer: (SHOW ANSWER)

NEW QUESTION: 89

As shown in the figure below, R1, R2, and R3 have enabled IPv6 in the ISIS process and established a Level2 neighbor relationship. Which of the following statements are correct about the IP routing table of R3? (Multiple choice)

- A. 2021:: /64 route will appear in the IP routing table
- B. 2019:: /64 route will appear in the IP routing table
- C. 2020:: /64 route will appear in the IP routing table
- D. The 2022:: /64 route will appear in the IP routing table

Answer: A,B,C,D (LEAVE A REPLY)

NEW QUESTION: 90

Which of the following statements about VLAN aggregation are correct? (Multiple questions)

- A. A Super VLAN can contain one or more Sub-VLANs
- B. Super Sub-VLAN contains physical interfaces, which can establish a three-layer VLANIF interface
- C. Sub-VLAN is used to isolate the broadcast domain
- D. Sub-VLAN contains physical interfaces, and can establish a three-layer VLANIF interface

Answer: A,C (LEAVE A REPLY)

NEW QUESTION: 91

Router R1 and Router R2 run BGP. Both routers are in the AS 65234. The route of router R2 exists in the BGP routing table of router R1, but is not in the IP routing table of router R1. So, what caused the problem?

- A. Synchronization is turned off
- B. The BGP neighbor relationship is Down.
- C. Router R1 does not enable BGP Multi-hop
- D. Routing is not optimal

Answer: D (LEAVE A REPLY)

Valid H12-261_V3.0-ENU Dumps shared by PrepPdf.com for Helping Passing H12-261_V3.0-ENU Exam! PrepPdf.com now offer the **newest H12-261_V3.0-ENU exam dumps**, the PrepPdf.com H12-261_V3.0-ENU exam **questions have been updated** and **answers have been corrected** get the **newest** PrepPdf.com H12-261_V3.0-ENU dumps with Test Engine here:

https://www.preppdf.com/Huawei/H12-261_V3.0-ENU-prepaway-exam-dumps.html

(485 Q&As Dumps, **40%OFF Special Discount: Exam-Tests**)

NEW QUESTION: 92

ICMPv6 has two types: Error Messages and Information Messages.

- A. TRUE
- B. FALSE

Answer: A (LEAVE A REPLY)

NEW QUESTION: 93

If there is a Huawei switch running the STP protocol, and now the G0/0/17 interface and G0/0/18 interface of the switch are connected by a cable, which of the following descriptions about this scenario is correct?

- A. Both the G0/0/17 interface and G0/0/18 interface will enter the Forwarding state
- B. Both the G0/0/17 interface and G0/0/18 interface will enter the Discarding state

- C. The G0/0/18 interface will continue to change back and forth between the listening state and the learning state
- D. The G0/0/18 interface will enter the Discard ing state
- E. The G0/0/17 interface will enter the Blocking state

Answer: D (LEAVE A REPLY)

NEW QUESTION: 94

By default, the switch configures the MAC address table to be empty. Host A connected to the switch sends the first unicast data frame. What operation will the switch perform after receiving the data frame?

- A. The switch records the source MAC address of the data frame and floods the data frame.
- B. The switch forwards the data frame out of an interface according to the destination MAC address of the data frame.
- C. The switch will discard the data frame
- D. The switch caches the data frame and waits for the destination host to send the data frame and then forward it.

Answer: A (LEAVE A REPLY)

NEW QUESTION: 95

Which of the following descriptions about the differences between IGMP versions are correct? (Multiple choice)

- A. IGMPv1/v2/v3 cannot support the SSM model
- B. IGMPv1/v2 cannot elect a querier by itself, while IGMPv3 can
- C. IGMPv1 does not support specific group queries, while IGMPv2 supports
- D. For members to leave, IGMPv2/v3 can leave actively, but IGMPv1 cannot

Answer: C,D (LEAVE A REPLY)

NEW QUESTION: 96

Which statement is correct about multicast packet forwarding?

- A. The source address of the multicast packet is a unicast address
- B. The IGMP Snooping function cannot control the range of multicast traffic flooding in the Ethernet
- C. In the multicast transmission mode, the destination address of the message can clarify the location of the receiver
- D. RPF check failure indicates that the multicast data packet is received from the sub-optimal interface, but the inbound interface will still receive the multicast traffic and forward it downstream

Answer: A (LEAVE A REPLY)

NEW QUESTION: 97

What is wrong about the description of the permanent multicast address?

- A. All hosts and routers in the network segment listen to 224.0.0.1
- B. All routers listen on 224.0.0.2
- C. All routers running PIM protocol listen to 224.0.0.100
- D. All routers running OSPF protocol listen on 224.0.0.5

Answer: ([SHOW ANSWER](#))

NEW QUESTION: 98

The two routers are connected through the serial port, but they cannot ping each other. Now check the port status as follows. Can you determine the cause from the above information?

- A. The link is not wide enough
- B. Subnet mask does not match
- C. Inconsistent link layer protocols at both ends
- D. The IP addresses of both ends are not on the same network segment

Answer: C ([LEAVE A REPLY](#))

NEW QUESTION: 99

The DHCP relay is responsible for forwarding DHCP messages between the DHCP server and the DHCP client, and assists the DHCP server to dynamically allocate the same network parameters to the DHCP client.

- A. FALSE
- B. TRUE

Answer: ([SHOW ANSWER](#))

NEW QUESTION: 100

The topology map and configuration are as follows. Now I hope that there is no detailed routing entry of 10.6.3.3/32 in the R1 routing table. Which of the following statements can achieve this requirement?

(Multiple Choice)

- A. Configure filter-policy on R2, match ACL 10.0.3.3/32, and apply it in the export direction.
- B. Configure filter-policy on R1, match ACL 10.0.3.3/32, and apply it in the import direction.
- C. Configure route summarization on R2 and summarize the routes to 10.0.0.0/16.
- D. Configure route summarization on R3 and summarize the routes to 10.0.0.0/16.

Answer: B,D ([LEAVE A REPLY](#))

NEW QUESTION: 101

If there is a run 802.1D spanning tree protocol Local Area Network. Which of the following parameters does non-root switch not receive from the root switch?

- A. MaxAge
- B. Hello time

- C. Hold time
- D. Root cost
- E. Forward delay

Answer: C ([LEAVE A REPLY](#))

NEW QUESTION: 102

The RSTP protocol provides a variety of protection functions. For example, when the edge port is configured in the protection state, the processing method after the edge port receives the BPDU message is:

- A. Forward BPDU packets as required
- B. Obtain relevant information after parsing the BPDU message
- C. Close the port
- D. Discard the BPDU message directly

Answer: ([SHOW ANSWER](#))

NEW QUESTION: 103

You want to set the DSCP value of VoIP traffic in HW network equipment to EF. According to the differentiated services model RFC, the flow mark EF should be set as

_____.

- A. IPTos is set to 0xEF
- B. IP Experimental ECN
- C. Bitstream 101110
- D. DSCP is set to decimal 5
- E. DSCP is set to decimal 36

Answer: C ([LEAVE A REPLY](#))

NEW QUESTION: 104

To achieve the traffic filtering function, you can use traffic-filter or MQC. Compared with traffic-filter, MQC can be called in more views.

- A. FALSE
- B. TURE

Answer: B ([LEAVE A REPLY](#))

NEW QUESTION: 105

ISIS does not send CSNP packets under the P2P network type during the neighbor establishment process.

- A. False
- B. True

Answer: A ([LEAVE A REPLY](#))

NEW QUESTION: 106

The following statements about the ISIS protocol route aggregation, which are correct?

- A. Route aggregation can only be configured on the level-1 router to take effect.
- B. Route aggregation can only be configured on the level-2 router to take effect.
- C. Route aggregation can be configured and validated on all types of routers.
- D. Route aggregation can only be configured on the level-1-2 router to take effect.

Answer: C (LEAVE A REPLY)

Valid H12-261_V3.0-ENU Dumps shared by PrepPdf.com for Helping Passing H12-261_V3.0-ENU Exam! PrepPdf.com now offer the **newest H12-261_V3.0-ENU exam dumps**, the PrepPdf.com H12-261_V3.0-ENU exam **questions have been updated** and **answers have been corrected** get the **newest** PrepPdf.com H12-261_V3.0-ENU dumps with Test Engine here:

https://www.preppdf.com/Huawei/H12-261_V3.0-ENU-prepaway-exam-dumps.html

(485 Q&As Dumps, **40%OFF Special Discount: Exam-Tests**)

NEW QUESTION: 107

When BGP EVPN Type2 routing is used to transmit IRB type routing, what does the information carried include? (Multiple choice)

- A. Layer 2 VNI
- B. Three-tier VNI
- C. Host IP address
- D. Host MAC address

Answer: A,B,C,D (LEAVE A REPLY)

NEW QUESTION: 108

What is the role of RT in MPLS VPN? (Multiple Choice)

- A. Allow the peer CE to decide which VPNv4 routes to import into the specific VRF.
- B. Allow the peer PE to decide which VPNv4 routes to import into the specific VRF.
- C. Allow the peer PE to decide which VPNv4 routes will not be imported into the specific VRF.
- D. Allow the peer CE to decide which VPNv4 routes will not be imported into the specific VRF.

Answer: B,C (LEAVE A REPLY)

NEW QUESTION: 109

Which of the following description of BGP neighbors are wrong? (Multiple questions)

- A. BGP router supports automatic neighbor discovery
- B. BGP needs to establish a UDP connection before establishing neighbors
- C. BGP needs to exchange link state information to establish neighbor relationships

D. MD5 authentication must be configured for BGP to establish neighbors

Answer: ([SHOW ANSWER](#))

NEW QUESTION: 110

The following statement about the NSSA area, which is correct?

A. In the OSPF neighbor relationship sent by the OSPF neighbor, the N position in the option field is set to 1. The E position is 0.

B. The NSSA area generates seven types of LSAs to advertise external routes. The FA address in the seven types of LSAs is used to prevent loops.

C. The OSPF neighbor in the NSSA area sends the hello text. The N position in the option- field is 0, and the E position is 1.

D. A default LSA must be automatically generated in the NSSA area to access the external network.

Answer: A ([LEAVE A REPLY](#))

NEW QUESTION: 111

We can use basic community-filters or advanced community-filters to filter BGP routes. Which of the following tools make the advanced community-filter more flexible than the basic community [1] filters?

A. Regular expression

B. IP-prefix

C. ACL

D. AS-path-filter

Answer: ([SHOW ANSWER](#))

NEW QUESTION: 112

When configuring source NAT with no-pat configuration parameters, which of the following statements is correct?

A. Only source IP address translation

B. Only the destination IP address translation session and dynamic BFD session

C. Perform destination IP address and destination port conversion

D. Simultaneous conversion of source IP address and source port

Answer: ([SHOW ANSWER](#))

NEW QUESTION: 113

One BD in VXLAN can correspond to multiple VNIs.

A. True

B. False

Answer: B ([LEAVE A REPLY](#))

NEW QUESTION: 114

BGP routing policy can control the distribution and reception of routes.

A. TRUE

B. FALSE

Answer: A ([LEAVE A REPLY](#))

Valid H12-261_V3.0-ENU Dumps shared by PrepPdf.com for Helping Passing H12-261_V3.0-ENU Exam! PrepPdf.com now offer the **newest H12-261_V3.0-ENU exam dumps**, the PrepPdf.com H12-261_V3.0-ENU exam **questions have been updated** and **answers have been corrected** get the **newest** PrepPdf.com H12-261_V3.0-ENU dumps with Test Engine here:
https://www.preppdf.com/Huawei/H12-261_V3.0-ENU-prepaway-exam-dumps.html
(485 Q&As Dumps, **40%OFF** Special Discount: **Exam-Tests**)