

SAP.P-SECAUTH-21.v2022-08-02.q28

Exam Code:	P-SECAUTH-21
Exam Name:	Certified Technology Professional - System Security Architect
Certification Provider:	SAP
Free Question Number:	28
Version:	v2022-08-02
# of views:	1264
# of Questions views:	280
https://www.freeqas.com/qa/SAP/P-SECAUTH-21/SAP.P-SECAUTH-21.v2022-08-02.q28.html	

NEW QUESTION: 1

What are the key capabilities of Event Analyzer in Enterprise Threat Detection 1.0? Note: There are 2 correct answers to this question.

- A. Baseline detection
- B. Synchronization of user contexts from ABAP Systems
- C. Pseudonymize user identities for data protection
- D. Predictive threat notification

Answer: A,C (LEAVE A REPLY)

NEW QUESTION: 2

Which authorizations should you restrict when you create a developer role in an AS ABAP production system? Note: There are 2 correct answers to this question.

- A. The ability to use the ABAP Debugger through authorization object S_DEVELOP
- B. The ability to execute class methods through authorization object S_PROGRAM
- C. The ability to execute function modules through authorization object S_DEVELOP
- D. The ability to execute queries through authorization object S_OUERY

Answer: A,C (LEAVE A REPLY)

NEW QUESTION: 3

You have implemented CUA in your organization and you want to set the field distribution attribute as follows: Maintain a default value in the central system that is automatically distributed to the child systems when you create a user. After distribution, the data is maintained only locally and is no longer distributed if you change it in the central or child system. Which field distribution parameter do you maintain?

- A. Proposal
- B. Global

- C. Local
- D. Redistribution

Answer: A (LEAVE A REPLY)

NEW QUESTION: 4

What is the SAP Best Practice to delete a security SAP role in SAP landscape?

- A. Delete the SAP role in all clients using Profile Generator
- B. Delete the SAP role in all clients in all systems using Profile Generator
- C. Transport the SAP role and delete the role using Profile Generator
- D. Delete the SAP role using Profile Generator, and then put it in the transport

Answer: (SHOW ANSWER)

NEW QUESTION: 5

A system user created a User1 and a schema on the HANA database with some data. User2 is developing modelling views and requires access to objects in User1's schema. What needs to be done?

- A. ROLE ADMIN needs to be granted to User2
- B. System user should grant User2 with SELECT privilege to User1 schema
- C. User2 needs to be granted with the same roles like User1
- D. User1 should grant _SYS_REPO with SELECT WITH GRANT privilege

Answer: (SHOW ANSWER)

NEW QUESTION: 6

Which authorization object controls access to the trusting system between the managed system and SAP Solution Manager?

- A. S_SERVICE
- B. S_RFC
- C. S_RFCACL
- D. S_ICM

Answer: C (LEAVE A REPLY)

NEW QUESTION: 7

You want to configure SNC with X.509 certificates using Common CryptoLib as the cryptographic library in a new installed AS ABAP system. Besides running SNCWIZARD, what do you need to set up for this scenario? Note: There are 2 correct answers to this question.

- A. Set the environment variable CCL_PROFILE to the default profile file path
- B. Set the environment variable CCL_PROFILE to SECUDIR
- C. Maintain the relevant CCL/SNC profile parameters
- D. Set the CCL SNC parameters using sapgenpse

Answer: A,C (LEAVE A REPLY)

NEW QUESTION: 8

You verified the password of the TMSADM user in your SAP landscape to be SAP defaulted. You want to reset this password by using program TMS_UPDATE_PWD_OF_TMSADM. What steps would you take to reset this password?

Note: There are 2 correct answers to this question

- A. Deactivate the SNC opt on
- B. Run this program in the Domain Controller (client 000)
- C. Assign "SAP_ALL" to TMSADM in all systems/clients including 000
- D. Lock TMSADM in all the system/clients including 000

Answer: B,D ([LEAVE A REPLY](#))

NEW QUESTION: 9

Insufficient authorization checks might allow A BAP programs to access the PSE files. Which authorization objects should we check to protect the PSEs? Note: There are 2 correct answers to this question.

- A. S_DATASET
- B. S_RZL_ADM
- C. S_DEVELOP
- D. S_ADMI_FCD

Answer: A,B ([LEAVE A REPLY](#))

NEW QUESTION: 10

The SAP HANA database has its parameters configured with its default values. How can the SAP_INTERNAL_HANA_SUPPORT catalog role be used?

- A. The role can be granted to another role (nested)
- B. The role can be granted to the SYSTEM user
- C. The role can be granted to multiple users at a time
- D. The role can be granted only with system privileges

Answer: B ([LEAVE A REPLY](#))

NEW QUESTION: 11

What are the features of the Audit Information System (AIS)? Note: There are 2 correct answers to this question.

- A. It can be launched directly using transact on SECR
- B. The roles are built from nodes in the Implementation Guide (IMG)
- C. The report selection variables are configured during setup
- D. It offers two types of audit reports: system and business

Answer: C,D ([LEAVE A REPLY](#))

NEW QUESTION: 12

You want to launch classic SAP GUI transactions directly from the SAP Fiori Launchpad. Which of the following scenarios do you choose?

- A. Chrome, SAP Cloud Platform, SAP GUI for Java
- B. Internet Explorer, SAP Business Client, SAP GUI for Windows
- C. Internet Explorer, ABAP front-end server, SAP GUI for Windows
- D. Chrome, SAP Enterprise Portal, SAP GUI for Java

Answer: C (LEAVE A REPLY)

NEW QUESTION: 13

User1 grants role 1 to user2. Who can revoke role 1 role from user2?

- A. The owner of role 1
- B. Only User1
- C. Any user with the 'ROLE ADMIN' database role
- D. The system OBA user

Answer: C (LEAVE A REPLY)

NEW QUESTION: 14

Which OData authorizations are required for a user to see business data in the SAP Fiori Launchpad? Note: There are 2 correct answers to this question.

- A. Access authorization in the SAP Fiori front-end system
- B. Start authorization in the SAP Fiori front-end system
- C. Access authorization in the SAP S/4HANA back-end system
- D. Start authorization in the SAP S/4HANA back-end system

Answer: B,C (LEAVE A REPLY)

NEW QUESTION: 15

What reference is used to connect multiple Cloud Connectors to one SAP Cloud Platform subaccount?

- A. Location ID
- B. Virtual Host
- C. System Alias
- D. Instance ID

Answer: (SHOW ANSWER)

NEW QUESTION: 16

The SSO authentication using X.509 client certificates is configured. Users complain that they can't log in to the back-end system. The trace file shows the following error message: "HTTP request [2/5/9] Reject untrusted forwarded certificate". What is missing in the configuration? Note: There are 2 correct answers to this question.

- A. On the back-end, the profile parameter icm/HTTPS/verify client must NOT be set to 0

- B. On the web-dispatcher, the SAPSSLS.pse must be signed by a trusted certification authority
- C. On the web-dispatcher, the profile parameter icm/HTTPS/verify_client must be set to 0
- D. The web dispatcher's SAPSSLC.PSE certificate must be added to the trusted reverse proxies list in icm/trusted_reverse_proxy_<xx>

Answer: A,B (LEAVE A REPLY)

Valid P-SECAUTH-21 Dumps shared by PrepPdf.com for Helping Passing P-SECAUTH-21 Exam! PrepPdf.com now offer the **newest P-SECAUTH-21 exam dumps**, the PrepPdf.com P-SECAUTH-21 exam **questions have been updated** and **answers have been corrected** get the **newest** PrepPdf.com P-SECAUTH-21 dumps with Test Engine here: <https://www.preppdf.com/SAP/P-SECAUTH-21-prepaway-exam-dumps.html> (80 Q&As Dumps, **40%OFF Special Discount: Exam-Tests**)

NEW QUESTION: 17

You have implemented CUA in your organization and you only want to compare the company address data between the central system and child systems to perform the synchronization activities. Which transact on do you use for comparing the company address between these systems?

- A. SCUC
- B. SUCOMP
- C. SCUM
- D. SCUG

Answer: (SHOW ANSWER)

NEW QUESTION: 18

For which purpose do you use instance Secure Storage File System (SSFS) in an SAP HANA system? Note: There are 2 correct answers to this question.

- A. To store the secure single sign-on configuration
- B. To protect the X.509 public key infrastructure certificates
- C. To store root keys for data volume encryption
- D. To protect the password of the root key backup

Answer: C,D (LEAVE A REPLY)

NEW QUESTION: 19

Your customer runs a 3-tier environment You are asked to set up controls around monitoring the sensitive objects (such as programs, user-exits, function modules) in a development system before they are transported to the quality assurance system.

Which table would you maintain to monitor such sensitive objects before executing an import?

- A. TMSTCRI
- B. TMSCEDES
- C. TMSBUFFER
- D. TMSMCONF

Answer: ([SHOW ANSWER](#))

NEW QUESTION: 20

In addition to the authorization /UI2/LAUNCHPAD, which other authorizations are required to assign to an SAP Fiori Launchpad user? Note: There are 2 correct answers to this question.

- A. /UI2/INTEROP
- B. /UI2JPAGE_BUILDER_PERS
- C. /UI2JPAGE_BUILDER_CUST
- D. /UI2/FLC

Answer: ([SHOW ANSWER](#))

NEW QUESTION: 21

You have a load balancer in a DMZ network zone (called natl.mydomain.com) in front of 2 SAP NetWeaver AS systems (host1.mydomain.com, host2.mydomain.com). What is the recommended common name part of the distinguished name on the SSL Server's PSE?

- A. It should be a combined DNS alias for host 1.mydomain.com and host2.mydomain.com and nat1.mydomain.com
- B. It should be natl.mydomain.com
- C. It should be *.mydomain.com (wildcard) names
- D. It should be host 1.mydomain.com, host2.mydomain.com individually for each PSE

Answer: ([SHOW ANSWER](#))

NEW QUESTION: 22

Which Object ID is used to integrate Business Rule Framework (BRF+) to Multi Step Multi Process (MSMP) initiator workflow?

- A. Expression ID
- B. Process ID
- C. Application ID
- D. Function ID

Answer: D ([LEAVE A REPLY](#))

NEW QUESTION: 23

Why do you use table logging in AS ABAP?

- A. To log changes in master data

- B. To log changes in application data
- C. To log changes in table technical settings
- D. To log changes in customizing tables

Answer: D ([LEAVE A REPLY](#))

NEW QUESTION: 24

You have configured a Gateway SSO authentication using X.509 client certificates. The configuration of the dual trust relationship between client (browser) and SAP Web Dispatcher as well as the configuration of the SAP Web Dispatcher to accept and forward client certificates were done. Users complain that they can't log in to the back-end system. How can you check the cause?

- A. Run gateway transaction /IWFND/TRACES
- B. Run gateway transaction /IWFND/ ERRORJ.OG
- C. Run back-end system trace using ST12
- D. Run back-end transaction SMICM and open the trace file

Answer: ([SHOW ANSWER](#))

NEW QUESTION: 25

Which basis transaction provides an optimized user interface for evaluating authorization checks only?

- A. RSECADMIN
- B. STAUTHTRACE
- C. ST01
- D. ABAP_TRACE

Answer: B ([LEAVE A REPLY](#))

NEW QUESTION: 26

Which data source needs to be integrated into SAP Identity Management via the Virtual Directory Server (VOS)?

- A. AS ABAP
- B. LDAP
- C. AS Java
- D. SAP HCM

Answer: ([SHOW ANSWER](#))

NEW QUESTION: 27

How can you protect a table containing sensitive data using the authorization object S_TABU_DIS?

- A. The tables containing sensitive data must be associated with table groups in table TBRG.

- B.** The field DICBERCLS of the authorization object must enumerate all table names of the tables containing sensitive data.
- C.** Authorization table groups containing tables with sensitive data must be defined in table TDDAT and these must be omitted for all employees who do not need access to these tables
- D.** The tables containing sensitive data must be named using the authorization object S_TABU_DIS for all responsible administrator employees. The fields DICBERCLS of the object S_TABU_DIS can

Answer: C (LEAVE A REPLY)

then be filled with *.

NEW QUESTION: 28

A security consultant has activated a trace via ST01 and is analyzing the authorization error with Return Code 12. What does the Return Code 12 signify?

- A.** "Objects not contained in User Buffer"
- B.** "No authorizations and does NOT have authorization object in their buffer"
- C.** "Too many parameters for authorization checks"
- D.** "No authorizations but does have authorization object in their buffer"

Answer: B (LEAVE A REPLY)

Valid P-SECAUTH-21 Dumps shared by PrepPdf.com for Helping Passing P-SECAUTH-21 Exam! PrepPdf.com now offer the **newest P-SECAUTH-21 exam dumps**, the PrepPdf.com P-SECAUTH-21 exam **questions have been updated** and **answers have been corrected** get the **newest** PrepPdf.com P-SECAUTH-21 dumps with Test Engine here: <https://www.preppdf.com/SAP/P-SECAUTH-21-prepaway-exam-dumps.html> (80 Q&As Dumps, **40%OFF** Special Discount: **Exam-Tests**)