

C. 5 segments

D. 2 segments

Answer: C ([LEAVE A REPLY](#))

NEW QUESTION: 3

Which deployment model ensures that management and control plane is cloud-delivered while data continues to flow on-premises between VMware SD-WAN nodes that remain on-premises?

A. Hosted SD-WAN Orchestrator/Controller

B. All on-premises

C. Partially on-premises

D. On-premises SD-WAN Orchestrator/Controller

Answer: B ([LEAVE A REPLY](#))

NEW QUESTION: 4

An Enterprise customer just acquired a new company, and the Network Enterprise administrator was tasked to integrate over 20 new branches into their existing SD-WAN network. However, these branches have overlapping IPs with the existing branches subnets.

A. Configure a NAT firewall rule in each branch, translating its subnets into a new non-overlapping subnet

B. Configure a policy based NAT for each branch translating its subnets into a new non-overlapping subnet

C. Configure a LAN-side NAT rule at the branch device settings, translating its subnets into a new non-overlapping subnet

D. Configure a NAT hand off rule at the VMware SD WAN gateway assigned to these new branches, translating the new branch subnets into a new non-overlapping subnet

Answer: ([SHOW ANSWER](#))

NEW QUESTION: 5

Given a VMware SD WAN Branch Edge with Dual Internet links A and B:

* Link A has 50 Mb capacity and latency 10ms

* Link B has 50 Mb capacity and latency 10ms

A database backup of 40Mbps is started, and the traffic classified as low priority bulk traffic.

Which statement is correct?

A. Packets will be sent out the highest latency link first as this is low priority bulk traffic

B. Packet duplication will take place to ensure both links are optimized.

C. Link Aggregation may take place, and both links could be used.

D. DMPO will perform per flow load balancing.

Answer: C ([LEAVE A REPLY](#))

NEW QUESTION: 6

During a VMware SD-WAN design session for a core business application, a customer expressed the following requirements:

* Allow business abstraction so that similar policies can be applied across different hardware types.

* Eliminate the need for the operations team to know the type of physical connectivity or the WAN carrier.

* Maintain SLA for real-time application.

Which design should be taken in terms of Link Steering?

A. Deselect Error Correct before Steering Defaults.

B. Select Error Correct Before Steering with % definition

C. Select WAN Link, and then define the DSCP tagging

D. Select Transport Group, and then select Preferred option.

Answer: C ([LEAVE A REPLY](#))

NEW QUESTION: 7

What is a typical use case for the deployment of a VMware SD-WAN Partner Gateway?

A. Provide multi-transport in a service provider backbone for interconnecting a global customer SD-WAN branches.

B. Provide connectivity between multiple enterprise customers over private circuits

C. Get improved flow analytics for all traffic in the SD-WAN network

D. Interconnect branches/remote sites of a single enterprise customer to the internet

Answer: A ([LEAVE A REPLY](#))

NEW QUESTION: 8

A customer is using hypervisor to install VMware Partner Gateways.

Which two hypervisors may be used? (Choose two.)

A. KVM

B. Kubernetes

C. Hyper-V

D. ESXi

E. XenServer

Answer: ([SHOW ANSWER](#))

NEW QUESTION: 9

A VMware SD-WAN customer has a requirement to enable single sign-on (SSO) authentication to their existing provider (IdP) for access to their Orchestrator account.

Which authentication protocol is supported?

A. TACACS+

B. OpenID Connect (OIDC)

C. LDAP

D. SAML 2.0

Answer: ([SHOW ANSWER](#))

NEW QUESTION: 10

Which VMware SR-WAN component runs the Deep Application Recognition Engine?

- A. VMware SD-WAN Controller
- B. VMware SD-WAN Edge
- C. VMware SD WAN Orchestrator
- D. VMware SD-WAN Gateway

Answer: ([SHOW ANSWER](#))

NEW QUESTION: 11

Company A has recently acquired Company B and needs to establish network connectivity. Company A has only Cisco for firewalls and VPN. Company B is using VMware SD-WAN. Which VMware SD-WAN Cloud VPN solution should an administrator configure to establish connectivity?

- A. Branch to Non VMware SD-WAN Site.
- B. Branch to Main Office VPN
- C. Branch to SD-WAN Hub
- D. Branch to Branch VPN

Answer: ([SHOW ANSWER](#))

NEW QUESTION: 12

A service provider wants to offer a common service from its data center via VMware SD-WAN Partner Gateway to many customers with overlapping IP addresses. Which configuration must be implemented?

- A. Enable tag type QinQ under hand off interface configuration
- B. Enable NAT hand off under hand off static routes configuration
- C. Define multiple segments for each customer
- D. Configure source policy-based NAT under business- policies configuration

Answer: C ([LEAVE A REPLY](#))

NEW QUESTION: 13

A service provider assigns two Partner Gateways to a VMware SD-WAN Edge. Which description is correct about default route.

- A. The service provider administrator decides whether the Partner Gateway advertises a default route 0.0.0.0/0 or not, although it is advertised by default.
- B. A default route 0.0.0.0/0 can be configured as a static route and set to NAT only on the Gateway
- C. When handoff is turned off on a Partner Gateway, the Gateway does not advertise a default route 0.0

0.0/0 to the Edge.

D. Its default route 0.0.0.0/0 has been configured for both Gateways, internet traffic originated from the Edge can failover to the other Gateway in case of a Gateway failure.

Answer: B (LEAVE A REPLY)

NEW QUESTION: 14

A customer is migrating a branch site with a VMware SD-WAN Edge coexisting with the CE. The Edge will be connected to internet link directly while connecting to the CE via a Layer 3 LAN switch.

MPLS underlay is the preferred path for communication from this site to branch sites that have no VMware SD-WAN Edges. Communication from this site to branch sites that have VMware SD-WAN Edges should go through overlay.

A. Use BGP as the routing protocol on the Edge and flag its BGP neighbor to GE as Uplink.

B. Use BGP as the routing protocol on UK Edge and flag its BGP neighbor to the Layer 3 LAN switch as Uplink.

C. Use BGP as the routing protocol on the Edge and flag its BGP neighbor to PE as Uplink.

D. Use BGP as the routing protocol on the Edge and filter prefixes from CE using Uplink Community

Answer: C (LEAVE A REPLY)

NEW QUESTION: 15

A network architect is designing a VMware SD-WAN architecture for customer using VMware hosted VCO and VCGs, while VCEs will be deployed at the customer's branches and data centers. The network architect would like to achieve control plane redundancy.

Which action, if any, should be taken to meet this goal?

A. VCGs automatically assigned to a VCF. do not participate in control plane At least two dedicated Controllers should be manually assigned for each VCGs to achieve control plane redundancy.

B. Multiple VCGs are automatically assigned to every VCE and control plane on VCU is always enabled, so control plane redundancy has been taken care of already

C. VCGs automatically assigned to a VCE do not participate in control plane At least two dedicated Controllers should be manually assigned for the customer to achieve control plane redundancy

D. Multiple VCFs at data centers can be configured to function as route reflectors to achieve control plane redundancy.

Answer: D (LEAVE A REPLY)

NEW QUESTION: 16

Which feature is required to prevent a split-brain condition for a branch in an Enhanced HA

A. VRRP

B. Split Brain Detection

C. Cloud VPN

D. SD-WAN Service Reachable on the private overlay

Answer: ([SHOW ANSWER](#))

Valid 5V0-42.21 Dumps shared by PrepPdf.com for Helping Passing 5V0-42.21 Exam! PrepPdf.com now offer the **newest 5V0-42.21 exam dumps**, the PrepPdf.com 5V0-42.21 exam **questions have been updated** and **answers have been corrected** get the **newest** PrepPdf.com 5V0-42.21 dumps with Test Engine here:
<https://www.preppdf.com/VMware/5V0-42.21-prepaway-exam-dumps.html> (53 Q&As Dumps, **40%OFF Special Discount: Exam-Tests**)

NEW QUESTION: 17

A customer would like to ensure that the traffic towards the Partner Gateway does not exceed a certain bandwidth.

Which feature should be used?

A. Change the application priority to low.

B. Enable the rate limit under a new custom Business Policy Rule.

C. Enable the SD-WAN Overlay Rate-Limit.

D. Modify the SD WAN Traffic Class and Weight Mapping

Answer: A ([LEAVE A REPLY](#))

Valid 5V0-42.21 Dumps shared by PrepPdf.com for Helping Passing 5V0-42.21 Exam! PrepPdf.com now offer the **newest 5V0-42.21 exam dumps**, the PrepPdf.com 5V0-42.21 exam **questions have been updated** and **answers have been corrected** get the **newest** PrepPdf.com 5V0-42.21 dumps with Test Engine here:
<https://www.preppdf.com/VMware/5V0-42.21-prepaway-exam-dumps.html> (53 Q&As Dumps, **40%OFF Special Discount: Exam-Tests**)